ASTRAGALS AND MEETING STILES

Locking Astragals – U.S. Patent Number 5,350,207 and Patent Number 5,328,217

- Weatherstripped astragals with locking spring bolts or slide bolts for 1-3/4" and 1-3/8" residential and office suite inswing double entrance doors.
- Each astragal comes complete with an installation kit and detailed instructions.
- Choose from two locking options: Odd numbered astragals have economical smooth acting slide bolts. Slide bolts are now 18 inches from the top/bottom for easier access. Even numbered astragals have locking spring bolts. Both have full 3/8" diameter steel bolts with 1-1/16" throw for improved locking strength. In the extended and locked position, locking spring bolts cannot be easily retracted by tampering. In the retracted position, the spring loaded bolts latch firmly, thus preventing marking of the floor and door header trim when opening or closing the inactive door.
- All styles are edge mounted on a square edge door.
- Choose from three style options: slimline, colonial and colonial with thermal break.
- The slimline style is available with a vinyl bulb (V) insert or SiliconSeal™ (S) insert. The colonial styles are available with Q102 or Q106 kerf-in foam (Q) insert or kerf-in magnetic (M) insert.
- Slimline style with slide bolt

3493_S

AVAILABLE FINISHES: BDG, C, D, G, PW, SN

3493 also available with 18" slide bolt (at additional cost) for easier access (specify "L" at the end of the product number for this option i.e. **3493** VL).

3493 V


AVAILABLE FINISHES: BDG, C, D, G, PW, SN

Slimline style with locking spring bolt

3494 S

AVAILABLE FINISHES: BDG, C, D, G, PW, SN


Slimline Style



- · All styles come with pile seal at inner door edge.
- Styles 3493 thru 3498 come with a molded sponge neoprene bottom seal.
- All feature four-way adjustable strike plate mounting for latchbolt and deadbolt (U.S. Patent Number 5,328,217).
- All come with a vinyl snap-in cover strip to conceal the cutout and cover the mounting screws.
- Astragal stock lengths are 80", 84", 96" and 120".
- A standard deadbolt punchout is 3/4" by 4" at 40" on center.
- · Punchout supplied on request only.
- For non-stock astragals, specify deadbolt punchout size and center distance from top end.
- Specify handing using the handing chart on page 82 or 85.

Oak Fascia

- Available in 96" length only; shorter lengths are invoiced at 96".
- An excellent alternative to locking wood astragals (3481, page 84), the oak fascia is attached to the face of 3493/3494 locking metal astragals, providing a warm aesthetic appearance while utilizing the mechanical advantages of the locking metal astragals.
- The oak fascia is attached to the face of the **3493/3494** using factory installed liquid nails.
- The oak fascia is supplied unfinished, to allow for custom matching.



Please refer to the listings under each product for stocked finishes. See the General Information section for a complete list of all Pemko stocked and non-stocked finishes. Contact the factory for the price and availability of non-stocked finishes.

AVAILABLE FINISHES FOR PRODUCTS SHOWN ON THIS PAGE (see General Information section for finish chart)

BDG (Bright Dip Gold Anodized) • C (Clear Anodized) • D (Dark Bronze Anodized) • G (Gold Anodized) PW (Painted White) • SN (Satin Nickel Anodized) • Special finishes available upon request