

AUTO REWIND HOSE REEL



Heavy Duty *Industrial!*

Air Hose Reel

Complete with

50' Air Tool Hose

- **Lifetime Warranty**
On hose and reel, separately - except "O" rings.
- **Solves hose storage problems**
Efficiently manage your supply hoses.
- **Easy payout, just grab it and go!**
- **Hang it on your wall or ceiling**
The mounting fixture is provided.
- **Mount it on your floor or bench**
An optional mounting fixture is available.
- **All hose included**
A 3' supply hose, for connection to your air supply and a 50' working hose with standard brass fittings. Both hoses have the same inside diameter and are rated at 300 psi working pressure.

Specials!

Power Port Auto Rewind Hose Reel

Put an end to your hose storage problems. Easy payout, just grab it and go! Each reel comes complete with 50' of Air Tool Hose and 3' Supply Hose for connection to your air supply. The hose has a smooth easy care finish on the outer cover. The heat resistant EPDM rubber hose is rated at 250 psi working pressure while the oil resistant PVC is rated at 300 PSI. working pressure. You can hang these from the wall or ceiling with the mounting fixture that is provided. If you want to mount it on the floor or your bench an optional fixture is available.

Lifetime Warranty.

All Retractable Air Hose Reels come complete with a 50' air tool hose and a 3' Supply hose.



MODEL	ID	DESCRIPTION	FITTINGS
HR 5038-ORS	3/8"	YELLOW PVC	1/4" MNPT
HR 5038-R	3/8"	RED EPDM	1/4" MNPT
HR 5038-B	3/8"	BLACK EPDM	1/4" MNPT
HR 5012-ORS	1/2"	YELLOW PVC	1/2" MNPT
HR 5012-R	1/2"	RED EPDM	1/2" MNPT
HR 5012-B	1/2"	BLACK EPDM	1/2" MNPT

Hose Reel Supplies and Accessories



PART	DESCRIPTION
HR FLR-MNT	HOSE REEL FLOOR / BENCH MOUNT
HR STD-MNT	HOSE REEL WALL / CEILING MOUNT
HR O RINGS	PAIR OF REPLACEMENT "O" RINGS

Power Port Air Tool Hose Caddy

End your hose storage problems. Easy to carry, lightweight, less than 25 lbs. Easy payout - just grab it and go! Reach anywhere on the job site. Available in both 1/4" or 3/8" NPT (National Pipe Thread) fittings. The oil resistant PVC (ORS) hose has a 300 PSI. working pressure, 1500 PSI Burst. Smooth easy care, oil resistant, non-marring outer cover with oil resistant inner tube. Premium Red or Black EPDM rubber and Medium grade Blue PVC available. **Lifetime Warranty**

All Caddy's come complete with air tool hose and a 5' Full Flow Swivel Supply hose.



MODEL	ID	LENGTH	FITTINGS
HC38100ORS	3/8"	100'	1/4" MNPT
HC38150ORS	3/8"	150'	1/4" MNPT
HC38100R	3/8"	100'	1/4" MNPT
HC38150R	3/8"	150'	1/4" MNPT
HC38100B	3/8"	100'	1/4" MNPT
HC38150B	3/8"	150'	1/4" MNPT
HC38100STB	3/8"	100'	1/4" MNPT
HC38150STB	3/8"	150'	1/4" MNPT

Replacement Full Flow Swivel Supply Hose

The Full Flow Swivel Supply Hose will require changing periodically, depending on wear, to assure continued high performance of the hose caddy.



MODEL	ID	LENGTH	COLOR
HC3805-R	3/8"	5'	RED
HC3805-B	3/8"	5'	BLACK
HC3805-ORS	3/8"	5'	YELLOW

Power Port Premium Oil Resistant Air Hose

A Lightweight non-marring oil & chemical resistant PVC blend of special elastomers produce a very tough, lightweight and flexible hose to convey air, water & some gases. Solid brass Male-by-Male NPT fittings and strain relief springs help to create the long life expectancy. The design strength of 300 PSI. working pressure, 1500 PSI. burst, provides an extra measure of strength, safety and durability. **Lifetime Warranty. Optional lengths and fittings available on all hoses.**



MODEL	ID	LENGTH	FITTINGS
AH 1425-ORS	1/4"	25'	1/4" MNPT
AH 1435-ORS	1/4"	35'	1/4" MNPT
AH 1450-ORS	1/4"	50'	1/4" MNPT
AH 14100-ORS	1/4"	100'	1/4" MNPT
AH 14BULK-ORS	1/4"	500'	BULK



AH 3825-ORS	3/8"	25'	1/4" MNPT
AH 3835-ORS	3/8"	35'	1/4" MNPT
AH 3850-ORS	3/8"	50'	1/4" MNPT
AH 38100-ORS	3/8"	100'	1/4" MNPT
AH 38BULK-ORS	3/8"	300'	BULK



AH 1225-ORS	1/2"	25'	1/2" MNPT
AH 1235-ORS	1/2"	35'	1/2" MNPT
AH 1250-ORS	1/2"	50'	1/2" MNPT
AH 12100-ORS	1/2"	100'	1/2" MNPT
AH 12BULK-ORS	1/2"	200'	BULK

Medium Grade Oil Resistant Hose.

Lightweight special thermal PVC. Standard assemblies complete with 1/4" NPT Male x Male brass fittings & strain relief springs to prevent premature wear at the end of each hose assembly. 250 PSI. working pressure 1200 PSI burst. (30 day Guarantee)



MODEL	ID	LENGTH	FITTINGS
AH 3825-STB	3/8"	25'	1/4" MNPT
AH 3835-STB	3/8"	35'	1/4" MNPT
AH 3850-STB	3/8"	50'	1/4" MNPT
AH 38100-STB	3/8"	100'	1/4" MNPT
AH 38BULK-STB	3/8"	300'	BULK

CUSTOM LENGTHS AND, OR, ANY COMBINATION OF FITTINGS OR COUPLINGS NEEDED ARE AVAILABLE.

Power Port Premium Heat Resistant Rubber Air Hose

Full four spiral tough polyester cord and EPDM (Ethylene Propylene Diene Monomer) age resistant cover prevents cracking and allows longer life. For air, water & some gases. 250 PSI Working pressure 1200 PSI. burst. Solid brass fittings and stainless steel strain relief springs add longer life and prevent premature wear at the end of each assembly. Available in both Red and Black rubber. **Lifetime Warranty**



MODEL	ID	LENGTH	FITTINGS
AH 3825R	3/8"	25'	1/4" MNPT
AH 3835R	3/8"	35'	1/4" MNPT
AH 3850R	3/8"	50'	1/4" MNPT
AH 38100R	3/8"	100'	1/4" MNPT
AH BULKR	3/8"	250'	BULK



AH 3825B	3/8"	25'	1/4" MNPT
AH 3835B	3/8"	35'	1/4" MNPT
AH 3850B	3/8"	50'	1/4" MNPT
AH 38100B	3/8"	100'	1/4" MNPT
AH BULKB	3/8"	250'	BULK

R = RED B = BLACK



AH 1250R	1/2"	50'	1/2" MNPT
AH 1250B	1/2"	50'	1/2" MNPT

1/2" Black not shown. Other lengths priced accordingly.

Couplings & Quick Disconnects

Fine fittings to make all your pneumatic hook ups quick and easy.



MODEL	SIZE	THREADS	DESCRIPTION	PRICE
DC20	1/4"	1/4" FNPT	QUICK COUPLING	
DCP20	1/4"	1/4" FNPT	AIR CHIEF PLUG	
DC21	1/4"	1/4" MNPT	QUICK COUPLING	
DCP21	1/4"	1/4" MNPT	AIR CHIEF PLUG	
DC2023	1/4"	3/8" FNPT	QUICK COUPLING	
DCP2023	1/4"	3/8" FNPT	AIR CHIEF PLUG	
DCP2103	1/4"	3/8" MNPT	AIR CHIEF PLUG	
DCP25	3/8"	3/8" MNPT	AIR CHIEF PLUG	
DC2502	3/8"	1/4" MNPT	QUICK COUPLING	
DCP2502	3/8"	1/4" MNPT	AIR CHIEF PLUG	
DC26	3/8"	3/8" FNPT	QUICK COUPLING	
DCP26	3/8"	3/8" FNPT	AIR CHIEF PLUG	
DC2622	3/8"	1/4" FNPT	QUICK COUPLING	
DCP2622	3/8"	1/4" FNPT	AIR CHIEF PLUG	
TF222	1/4" X	1/4" X 1/4"	FNPT BRASS TEE	
TF333	3/8" X	3/8" X 3/8"	FNPT BRASS TEE	

Power Port Nylon Recoil Hose

Lightweight, self-storing, space saving and eliminates possibility of tripping or tangling due to hoses being sprawled or dragged across work area. Resists oil, grease, corrosion, with heavy duty brass reusable fittings, 200 PSI. working pressure 1000 PSI. burst.

Lifetime Warranty



MODEL	ID	LENGTH	REUSABLE FITTINGS
RH1425	1/4"	25'	1/4" MNPT
RH3825W	3/8"	25'	1/4" MNPT
RH3850W	3/8"	50'	1/4" MNPT

Power Port "Lite-O-Matic" Retractable Cord Reels

Heavy duty 3 wire reels, Underwriters Laboratories listed with SVT 90 degree Celsius 6 and 10 amp ratings. These are grounding type reels with a rugged metal guard that's grounded. Most models have a power outlet in the handle which allows use as extension cord reel. Cyclolac unbreakable handle. See carton for instructions. **Lifetime Warranty**



MODEL	LENGTH	TYPE	DESCRIPTION
RL25-3	20'	18/3 SVT	6 AMP LITE
RL50-3	50'	18/3 SVT	6 AMP LITE

MODEL	LENGTH	TYPE	DESCRIPTION
RL35-3NS	35'	18/3 SVT	NO SWITCH LITE
RL30-3	30'	16/3	10 AMP LITE

ECR30-3	30'	16/3	10 AMP TRI-TAP
---------	-----	------	----------------

"Lite-O-Matic" Fluorescent Trouble Lights

15 watt energy miser bulb that puts off more light than 100 watt bulb. Unbreakable tube shield and heavy duty switch molded in the housing and grounded plug in ballast. Tubes out last bulbs 10 to 1. **Lifetime Warranty**



MODEL	WATTS	LENGTH	DESCRIPTION
FL 1525	15	25'	DROP LIGHT

MODEL	WATTS	LENGTH	DESCRIPTION
RFL 1540	15	40'	RETRACTABLE

“Lite-O-Matic” Shorty Fluorescent Lights

13 watt twin tube energy miser. Puts out 10 times more light than an incandescent bulb. Un-breakable tube shield plus heavy duty switch molded into the handle. Grounded plug-in ballast. 360 degree swivel hook. Tubes out last bulbs 10 to 1. **Lifetime Warranty**



MODEL	WATTS	LENGTH	DESCRIPTION
FLS 25	13	25'	DROP CORD
FLS50	13	50'	DROP CORD

MODEL	WATTS	LENGTH	DESCRIPTION
FLRS 20	13	20'	RETRACTABLE
FLRS 40	13	40'	RETRACTABLE
FLRS40NS	13	40'	RETR. NO SW.



Power Port “All Temp” Heavy Duty 15 Amp Drop Cord

All temperature 14 gauge, SJEOW-A, 3 wire grounding type cord, grounded metal cage, fully insulated molded handle with switch and power tap. Smooth easy clean cord. Use outdoors or indoors. Remains flexible to minus 50 degrees Celsius. See label for instructions.

Lifetime warranty



MODEL	LENGTH	TYPE	DESCRIPTION
TL1425-3	25'	14/3	15 AMP
TL1450-3	50'	14/3	15 AMP

Power Port 3-way Extension Cord

All temperature 12 gauge, SJEOW-A, 20 amp cord, 3 wire grounding type cord, molded connectors. Smooth easy clean cord with 3-way power tap. Use outdoors or indoors. Flexible to minus 50 degree Celsius. See label for instructions. **Lifetime Warranty**



MODEL	LENGTH	TYPE	DESCRIPTION
EC1250-3	50'	12/3 20A	15 AMP TRI-TAP
EC12100-3	100'	12/3 20A	15 AMP TRI-TAP

Power Port Pro-Boost Jumper Cables

Two, four and six gauge booster cables. Fine strand 100% copper for the ultimate in flexibility, maximum power transfer and longest life, The four and six gauge cables have non-marring color coded siamese cable with metal bands to prevent separation. Super flexible to minus 40 degrees Celsius. Color-coded 400 amp clamps with the cable connected directly to the jaws. Unique jaw design fits both post and side terminal batteries for quick and easy hook ups. Cable strain relief springs are built into the clamps to prevent wear and provide trouble-free use. Check cable tag for instructions. **Lifetime Warranty**



MODEL GAUGE LENGTH CLAMPS

BC612	6	12'	400 AMP
BC412	4	12'	400 AMP
BC420	4	20'	400 AMP



MODEL GAUGE LENGTH CLAMPS

BC220	2	20'	500 AMP PARROT
-------	---	-----	----------------

LED SCREWDRIVER & MAGNETIC TELESCOPING PICK UP TOOL



- 9 Bits to Cover Many Types of Screws with Convenient Bit Storage.
- Telescoping Magnetic Pick-Up Tool.
- Bits are Black Ionized Metal to Prevent Rusting.
- Easy to attach to Any Tool Belt.
- Ergonomically Designed Handle with Easy On/Off LED Light.



LED Cordless Rechargeable Work Light

32 LED LIGHT & 62 LED LIGHT

* 62 LED LIGHT COMES WITH

12V ADAPTER ALSO



Lifetime Warranty

- **FREE** Magnetic holder
- White LEDs for bright non-glare light
- Long life LEDs last over 80,000 hours in use
- Shatter proof housing and light shield
- Slim design fits into tight areas
- Supplied with 120V AC charger
- Lasts 5 hours on single charge
- Foldable swivel hook

Quantities may be limited

(Optional car charger available for for 32 LED's)

Dealers and Contractors PP2001-1

100' or 150' AIR TOOL HOSE REEL

Special!

Air Hose Caddy

- Lifetime Warranty
- Lightweight, less than 25 pounds
- Easy payout, just grab it and go!
- Reach anywhere on the job site
- End your hose storage problems
- Smooth easy care finish
- 300 lbs. Working Pressure



Wall Mount or Tote



Power Port Products, Inc.

301 W. Interstate Road, Addison, IL 60101

Voice 1-630-628-9102

Toll Free 1-800-TELE-REP

(1-800-835-3737)

Fax 1-630-543-7614

WEEKDAYS 8 AM TO 5 PM CST

Excellence in Service and Quality since 1978