Data/ Specification Sheet

KITCHEN ONE® MODEL KS6000 HAND PORTABLE EXTINGUISHER

FEATURES

- Contains 1.6 gal (6 L) of PYRO-CHEM® Wet Chemical Solution
- Meets or exceeds requirements of UL Standard 8 and Standard 711
- · Meets requirements of NFPA 10
- · Simple operation and maintenance
- · Wide angle, soft discharge spray pattern
- · Stainless steel bourdon tube gauge
- · Bar coded nameplate
- · Rechargeable
- Sold and serviced through a network of independent distributors in every state and most foreign countries
- UL rated 2-A:K
- Pre-filled and pressurized at the factory for convenient service ready to use – right out of the box

APPLICATIONS

The KITCHEN ONE® liquid agent fire extinguisher is specifically designed for use on fires that involve combustible cooking vegetable or animal fats in commercial cooking equipment. Typical appliances include; fryers; griddles, range tops; upright, natural charcoal, or chain-type broilers; electric, lava rock, mesquite or gas-radiant charbroilers and woks.

Newer, more efficient cooking appliances, plus the use of nonsaturated cooking oils, require a fire extinguishing agent which will not only smother a fire but provide a cooling effect.

The extinguisher is ideally suitable for use in restaurants, hospitals, nursing homes, hotels, schools, airports, and other similar facilities.

It is used as a backup to an automatic fire suppression system.

The energy source to the cooking equipment shall be shut off by the automatic fire suppression system in order to attain complete extinguishment and permit the cooking media to cool below its autoignition temperature.

DESCRIPTION

The KITCHEN ONE extinguisher is an attractive, easy to use and maintain, stainless steel extinguisher that will match commercial kitchen decor.

The PYRO-CHEM wet chemical solution fire extinguishing agent used in the extinguisher is a specially-formulated aqueous solution. It has been developed to provide rapid flame extinguishment and securement of hot fuels such as cooking shortenings. The refill agent is common to KITCHEN KNIGHT® II systems – no additional agent is needed to inventory.

CODES

Meets new Class K (Combustible Cooking Media) fire requirements of NFPA 10.



008132

SPECIFICATIONS

Model No.
 UL Rating
 Capacity
 Extinguisher
 Height
 Width
 Diameter
 KS6000
 2-A:K
 1.6 gal (6 L)
 21.25 in. (54.0 cm)
 9.5 in. (24.1 cm)

Range 8-10 ft (2.4-3.0 m)Discharge Time 54 seconds

• Temperature Range 32 °F to 120 °F (0 °C to 49 °C)

ORDERING INFORMATION

Part No. Description

552055 KITCHEN ONE KS6000

Wet Chemical Fire Extinguisher (UL)



PYRO-CHEM
One Stanton Street
Marinette, WI 54143-2542
715-732-3465
www.pyrochem.com

PYRO-CHEM is a trademark of Tyco International Ltd. or its affiliates.