



Box 459 - Rosemount, MN 55068
Phone 800-328-0953
Fax 800-334-8823

Sweeps - under door DB591

1. Measure the clearance at the bottom of the door. Measure the height of the door shoe that will be under the bottom of the door. It should be the same measure for proper operation of the door shoe. The door will have to be trimmed or threshold added to obtain this clearance.

2. Remove the door and measure its width.

3. Slide the gasketing material out of its aluminum retainer. Then cut the aluminum retainer to the width of the door. Trim the gasketing material to the same size.

4. Attach the metal retainer to the bottom of the door. Attach with the sheet metal screws provided, locating the screw in the center of the slotted holes in the metal retainer. This permits room for adjustment. When in position, tighten all the screws.

5. Slide the gasketing back in the retainer. When the gasketing is in, peen the retainer so that the gasketing cannot slide out.

6. Re-install the door.

7. Operate the door several times to insure the part is properly adjusted so as not to inhibit the door from self-closing and latching.



Positive Pressure Tested
Gasketing Materials for Fire
Doors. Intended for application
to/with listed steel frames
and/or classified steel covered
composite, hollow metal type
fire doors rated up to 3 hours,
wood and plastic covered com-
posite type fire doors rated up
to 1-1/2 hours, and wood core
type fire doors rated up to 20
minutes.

Meets UL10B, UL10C
Meets CAN4-S104-2010
Category J.

17L5 9903