

Model 428 Center Hung with Patch Fittings

Application

- Single Acting, Handed
- Exterior or Interior Doors
- Full Glass Doors
- Weight up to 325 lbs.
- Size Up to 3'2" x 8'0"



Product Description & Features

- Top and bottom patch fittings for tempered glass doors 3/8"-1/2" thick
- Built-in positive dead stop prevents door from swinging beyond the desired opening degree (*specify 85°, 90°, 95° or 105°*)
- Separate and independent valves for closing speed, latch speed and backcheck
- Available non-hold open (N) or selective hold open (S) at same degree as dead stop
- Delayed action available – prefix "DA" (*non-hold open closer only*)
- Models available to meet ICC/ANSI A117.1 low opening force requirements, prefix "PH". (*For 8-1/2 lbs. of opening force prefix "PH" and suffix "8-1/2 lbs."*)
- Cold weather fluid option – specify "CWF" (*not available for closers with "DA"*)
- Sealed closer option – specify "SC"
- Floor plate standard. For threshold application an extended spindle is required (*floor plate shown*)
- For extended spindles, contact the factory. No vertical adjustment
- Cylolac, rustproof cement case
- Frame stop required at header on lock side
- 605, 625 and 626 finishes only

Technical Information

Frame stop required at lock edge

