

HOW TO ORDER

1 Series	—	3 Door Size	36 Function/Base Metal	X Suffix/Options	630 Finish
1 - Hvy Dty Conc		1	16 - Friction		689 Sprayed Alum
1ADJ - Hvy Dty Conc Adj		2	26 - Holder		690 Sprayed Dk Brz
2 - Std Dty Conc Adj		3	36 - Stop		691 Sprayed Lt Brz
5 - Std Dty Conc Non-Adj		4	46 - Mult-func		696 Sprayed Brass
6 - Low Profile Conc		5			605 Bright Brass
6ADJ - Low Profile Conc Adj					606 Satin Brass
7 - Surf Cantilever Hldr			LS Less Spring (models 1 & 9 only)		611 Bright Bronze
8HD - Extra Hvy Dty Dbl Lever			5258 Standard Duty Bracket		612 Satin Bronze
9 - Hvy Dty Surf			5458 LH Heavy Duty Bracket		613 Dark Bronze
9ADJ - Hvy Dty Surf Adj			5459 RH Heavy Duty Bracket		613E Dark Oxidized
10 - Std Dty Surf Adj			Torx Security Screws		Satin Bronze - equivalent
55 - Std Dty Surf			R Arm Only		618 Bright Nickel
					619 Satin Nickel
					622 Flat Black
					629 Bright Stainless
					630 Stainless Steel
					652 Satin Chrome
					BSP Black Suede Powder Coat

SHIPPING WEIGHTS

Models	Shipping Weights
1, 1ADJ, 6, 6ADJ, 8HD, 9, 9ADJ	4.5 lbs.
2, 5, 10, 55	3.5 lbs.
7	7 lbs.

Less Spring – Suffix LS

Heavy-duty slide track type stops have a spring in the end of the channel that keeps the slider from deadstopping. If these units are being used with electromechanical closer, where the door, must deadstop, the LS option is needed. Available only with models 1 and 9

Angle Jamb Bracket Adapter

Standard-duty models suffix 5258 (non-handed)

Heavy-duty models suffix 5458 (LH) or 5459 (RH)

When surface mounted units are mounted on a rabbeted door on the push side, flush door and transom on the push side, or in a reverse installation on the pull side of the door, a special bracket is needed. Note: not all models can be mounted on the pull side of the door (see specific model numbers in catalog.)

Security Screws – Suffix Torx®

Security screws can be supplied for exposed fasteners



5258



5458/5459

