

Rockwood LP3301 - PostMount Locking Pull



Available Finishes:

- US3/605
- US4/606
- US10BE/613E
- US10BL/614
- US32/629
- US32D/630

Specifications:

FEATURES:

- Key operated from outside; turn piece on inside
- Cylinder options: Rim Cylinder, Small format interchangeable core housing: 7-pin (SFIC) less core and key (Standard), Small format interchangeable core housing w/ plastic construction core: 7-pin (SFIC), Customer Supplied Cylinder, Dummy Cylinder, or Privacy Function: keyless locking function
- Door types: $\frac{3}{8}$ " - $\frac{7}{8}$ " thick glass, 1 $\frac{3}{8}$ " - 2 $\frac{1}{2}$ " thick aluminum, hollow metal or wood doors
- Multiple locking options: floor, head or both
- Bolt location: 2" from face of door to centerline of bolt
- Bolt has $\frac{13}{16}$ " travel with fine adjustment
- Horizontal push/pull bar option

BENEFITS:

- Cylinder and thumbturn location eliminates physical strain when locking and unlocking
- Glass door applications secure the opening and allow for more natural light
- Bolt concealed inside pull provides a clean, streamlined look
- Simple door preparation allows for faster installation
- Suites with popular Rockwood door pulls, CORBIN RUSSWIN and SARGENT lever handles, McKINNEY hinges, creating a continuum of design
- Offers flexibility in custom sizes for a variety of applications