## Rockwood RM7310

## NeoMitre Pull Series

## Straight Pull without GripZone



Experience a safer and more open world

Customer Informa	ıtion						
Company Name:  Account #:  Email:				Date:			
				Phone/Fax:		/	
				PO #:	Line #:		
Door #'s:							
Quantity:			[				
∘ US32 <b>MS</b> ∘ BSP	<ul><li>US32/629</li><li>US32DMS</li><li>WSP</li><li>Coats (specify): _</li></ul>			3"	<b>→</b>	-1 <sup>1</sup> / <sub>4</sub> "	
Center to Center	(Maximum 118 ³/₄") <b>:</b>						
	o 2 (Standard) t recommended						
Door Type:	<ul><li>Glass</li></ul>	o Metal	o Wood				
Door Thickness:	o 1/2 <b>"</b> o Other:	0 1 3/4"	0 2 1/4"		Overall Height	Center to Center	
Hole Size (for glass of	door application onl	y) <b>:</b>					
<ul><li>Decorative Th</li><li>Back to Back</li><li>Concealed (N</li></ul>	etal/Wood Only) nru Bolt Metal/Wood Only nd Thru Bolt (Me	•					
Your signature indicates accurate and ready to b	the information cor be manufactured.	ntained on this orde	r form is				
(customer signature)							
(date)							

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424