



## Standard Duty Surface Mounted OH1000 Series

**Material:** Stainless steel.

**Finishes:** US32D.

**Fasteners:** Jamb: #12 x 1½" FH WS or #12-24 x ½" FH MS.  
Door: #12-24 x 1½" FH MS and ⅝" dia. sex bolt.

**Features:**

- Single acting doors.
- Non-handed.
- Slide track design.
- Recommended for medium traffic, medium weight doors.
- Degree of opening fully adjustable and can be adapted to changing needs.
- Heavy shock absorber spring provides compression before deadstop.
- Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in field. MF5012 KIT (Adapter kit) included.
- Complete screw packet with thru-bolts for door, wood and machine screws for frame.
- Torx® screws optional for security applications, but heavy-duty units should be considered for high-security applications.
- Durable slider cam and shock block.
- 110° maximum opening.
- ¾" square channel.
- Stop function UL listed for fire door assemblies.
- For pull side mounting or flush and rabbeted mounting on push side use angle jamb bracket adapter JB1000.

Door Opening					
No.	Function	Butts/Offset Pivots	Center Hung	Weight	ANSI A156.8
OH1001S	Stop only	18" - 24"	21" - 26½"	3.5 lbs.	C05542
OH1002S	Stop only	24½" - 30"	26¾" - 32"	3.5 lbs.	C05542
OH1003S	Stop only	30½" - 36"	32½" - 38"	3.5 lbs.	C05542
OH1004S	Stop only	36½" - 42"	38½" - 45"	3.5 lbs.	C05542
OH1005S	Stop only	42½" - 48"	45½" - 48"	3.5 lbs.	C05542
OH1001M	Multi-function	18" - 24"	21" - 26½"	3.5 lbs.	—
OH1002M	Multi-function	24½" - 30"	26¾" - 32"	3.5 lbs.	—
OH1003M	Multi-function	30½" - 36"	32½" - 38"	3.5 lbs.	—
OH1004M	Multi-function	36½" - 42"	38½" - 45"	3.5 lbs.	—
OH1005M	Multi-function	42½" - 48"	45½" - 48"	3.5 lbs.	—