



Automatic Flush Bolts No. 2840 (Automatic Top Bolt Only) No. 2842 (Set)

- Material:** Brass, stainless steel.
- Finishes:** US26D, US32D.
- Fastener:** No. 2842: 20 ea. #8x $\frac{3}{4}$ " FH combo screws, 2 ea. #6-8 plastic anchors.
No. 2840: 10 ea. #8x $\frac{3}{4}$ " FH combo screws. NOTE: No plastic anchor required for top only.
- Features:**
- For Fire Rated Metal Doors labeled A, B, C, D & E up to 4'w x 8'h.
 - Non-handed.
 - Fully automatic—opening active door retracts top and bottom bolts.
 - Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes.
 - Bolt head rods are adjustable up to 1 $\frac{1}{2}$ ".
 - Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- Options:** No. 2842 can be used with the No. 570 Dust Proof Strike (shown on page E4).

No.	Size	Weight	ANSI A156.3
2840	1" x 6 $\frac{3}{4}$ "	1.2 lbs.	Type 25
2842	1" x 6 $\frac{3}{4}$ "	2.4 lbs.	Type 25



Combination Flush Bolts No. 2805 (Self Latching Top Bolt Only) No. 2845 (Set)

- Material:** Brass, stainless steel.
- Finishes:** US26D, US32D.
- Fastener:** Top: 8 ea. #8 x $\frac{3}{4}$ " FH combo screws. NOTE: No plastic anchor required for top only.
Bottom (No. 2845 only) 18 ea. #8x $\frac{3}{4}$ " FH combo screws, 2 ea. #6-8 plastic anchors.
- Features:**
- For Fire Rated Metal Doors labeled A, B, C, D & E up to 4'w x 8'h.
- Top Bolt**
- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.
- Bottom Bolt (No. 2845 only)**
- Non-handed.
 - Fully automatic—opening active door retracts bottom bolt.
 - Override feature prevents damage to door or bolt if bolt head is blocked from entering strike.
 - Bolt head rod is adjustable up to 1 $\frac{1}{2}$ ".
 - Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- Options:** No. 2845 can be used with the No. 570 Dust Proof Strike (shown on page E4).

No.	Size	Weight	ANSI A156.3
2805	1" x 6 $\frac{3}{4}$ "	1.2 lbs.	Type 27
2845	1" x 6 $\frac{3}{4}$ "	2.4 lbs.	Type 27