



Lever Extension Flush Bolt
No. 556WS Windstorm

The Rockwood 556WS Flush Bolt is part of a UL certified assembly from ASSA ABLOY. The product MUST be used with the Ceco Trio, Curries 777 or the Fleming-Baron Trio series doors to meet certification. Recommended latching hardware includes Corbin Russwin ML2000, SARGENT 8200 or Yale® 8800 mortise locks, all with a latch bolt and a dead bolt.

- Material:** Brass and Stainless Steel.
- Finishes:** 26D or 32D.
- Fastener:** 8 ea. #8 - 32 x ¼" FH MS in Stainless Steel.
- Features:**
- ¾" bolt throw, ¾" rod backset.
 - 12" Stainless Steel rod length (center of face to bolt end retracted).
 - UL Certified.
 - Assembly approved for use in the state of Florida including the High Velocity Hurricane Zone (HVHZ).

No.	Size	Material	Weight	ANSI A156.16
556WS	Face plate: 1"x6¾" x 1⅛" Mortise Body 1" x 5-¼" x 1-⅜" Rod 12" x ½"D Strike: 1⅝" x 2¼" Guide: 1" x 2"	Brass Brass Stainless Steel Stainless Steel Stainless Steel	2.5 lbs./2	L04251



Lever Extension Flush Bolt
No. 557

- Material:** Cast brass.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** 7 ea. #8 x ¾" FH combo screws.
4 ea. #8 - 32 x ½" FH MS.
4 ea. #8 counter sunk washer.
- Features:**
- For Fire Rated Plastic & Wood Covered Doors measuring up to 4'w x 10'h rated up to and including 1½ Hours.
 - ¾" bolt throw, ¾" backset; door strength maintained by corner reinforcing plate.
- Options:** Use No. 570 Dust Proof Strike (shown on page E4) to prevent dirt blocking bottom strike.

No.	Size	Weight	ANSI A156.16
557	Face plate: 1"x6¾" Strike: 1⅝" x 2¼"	1.7 lbs./2	L04261



Lever Extension Flush Bolt With Bottom Fire Bolt
No. 557 x 19BFB

- Material:** Flush bolt - brass.
Bottom fire bolt - stainless steel.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** 7 ea. #8 x ¾" FH combo screws.
4 ea. #8 - 32 x ½" FH MS.
4 ea. #8 counter sunk washer.
- Features:**
- For Fire Rated Plastic & Wood Covered Fire Doors measuring up to 4'w x 9'h rated up to 20 minutes.
 - ¾" bolt throw, ¾" backset; door strength maintained by corner reinforcing plate.
 - When door is subjected to 230°F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together.
 - Bottom fire bolt eliminates need for floor prep.
 - Oversize fire bolt strike hole allows for slight door misalignment.

No.	Size	Weight
557 x 19BFB	Top bolt: 1"x6¾" Bottom bolt: 1⅜" dia.	0.9 lbs.



Dust Proof Strike No. 570

- Material:** Brass.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** Adjustment nut.
Spanner wrench.
2 ea. #8 x 1 OH SMS, 2 ea. plastic anchors.
2 ea. #8 - 32 x ¾" OH MS, 2 ea. lead anchors.
- Features:**
- Works with all Rockwood manual and automatic flush bolts.
 - Removable face plate for use with thresholds.
 - Adjustable height for carpeted areas.

No.	Size	Weight	ANSI A156.16
570	Face plate: 1⅜" x 2⅞" Barrel: ⅞" dia. x 2" depth	0.4 lbs.	L04021



Gravity Door Coordinator No. 576

- Material:** Cast brass.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** Body: 2 ea. #10 x 1" FH SMS, 2 ea. #10 - 24 x 1" FH MS.
Strike: 5 ea. #8 x 1" FH SMS.
- Other:**
- For use on door sizes:
 - with Astragal on active door - 18" to 48".
 - with Astragal on inactive door - 18" to 34".
 - with Astragal on both doors - 18" to 30".
 - The overlap of the astragal is maximum ⅞" with door hung on standard hinges. Customer must contact the factory for all other astragal situations.
- Features:** Non-handed reversible. Prevents the active door from closing until the inactive door is closed.

No.	Size	Projection	Weight	ANSI A156.3
576	1" x 5⅞"	7"	2.2 lbs.	Type 21