

800-458-2424 www.rockwoodmfg.com





### Roller Latch with Cast Strike No. 590

Material: Cast brass.

Features:

Finishes: Available in standard architectural finishes (see page 9).

Fastener: Body: 2 ea. #8x¾" FH combo screws.


Strike: 2 ea. #8×¾" FH combo screws.


Simple adjustment for roller projection.

• Solid nylon roller for durable silent operation.

No.	Latch Face	Strike	Weight	ANSI A156.16
590	1"×3¾"	1 <sup>11</sup> / <sub>16</sub> "×2 <sup>1</sup> / <sub>4</sub> "	0.6 lbs.	E09091







Ο

# Roller Latch with Double Acting Strike No. 590DA

Material: Brass.

Other:

Finishes: Available in standard architectural finishes (see page 9).

Fastener: Body: 2 ea. #8×¾" FH combo screws. Strike: 4 ea. #8×¾" FH combo screws.

For use on double acting doors and frames with the No. 590.

Specify size required.

Features: • Solid nylon roller for durable silent operation.

Simple adjustment for roller projection.

No. La	atch Face	Strike	Weight
590DA 1'	"×3¾"	2¾"xspecify	0.6 lbs.





### Roller Latch with ASA Strike No. 591

Material: Cast brass.

Finishes: Available in standard architectural finishes (see page 9).

Fastener: Body: 2 ea. #8×¾" FH combo screws.

Strike: 2 ea. #12-24x½" FH MS.

**Features:** • Solid nylon roller for durable silent operation.

Simple adjustment for roller projection.

No.	Latch Face	Strike	Weight	
591	1"×3¾"	1¼"×4½"	0.6 lbs.	





# Roller Latch with No. 161 Strike No. 592

Material: Cast brass.

Features:

Finishes: Available in standard architectural finishes (see page 9).

Fastener: Body: 2 ea. #8x¾" FH combo screws. Strike: 2 ea. #8x¾" FH combo screws.

Solid nylon roller for durable silent operation.

Simple adjustment for roller projection.

 No.
 Latch Face
 Strike
 Weight

 592
 1"×3¾"
 1½"×2¾"
 0.6 lbs.





# Roller Latch with Angle Stop No. 593

Material: Cast brass.

Finishes: Available in standard architectural finishes (see page 9).

Fastener: Body: 2 ea. #12×1½" FH WS.

Strike: 2 ea. #8×¾" FH combo screws.

• Mounts in header with strike in top of door.

Solid nylon roller for durable silent operation.

Simple adjustment for roller projection.

No.	Latch Face	Strike	Projection	Weight	ANSI A156.16	
593	1½"x4½"	11/8"×21/4"	<u>5</u> ⁄8"	0.8 lbs.	E09111	





# Roller Latch with No. 161 Strike No. 594

Material: Cast brass.

Features:

Finishes: Available in standard architectural finishes (see page 9).

Fastener: Body: 2 ea. #8x¾" FH combo screws. Strike: 2 ea. #8x¾" FH combo screws.

Solid nylon roller for durable silent operation.
Simple adjustment for roller projection.

Latch Face Strike

No.	Latch Face	Strike	Weight	
594	1½"×2½"	1½"×2¾"	0.7 lbs.	