



Heavy Duty Security Flush Pull No. D89

Material: Cast brass.

Finishes: Available in US4 and US26D (see page 9).

Fastener: ¼ - 20 × ½" OH Security Torx MS.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
D89	4" × 5"	1¼" × 3¼"	⅞"	1.3 lbs.	J403



Cylinder Pulls No. 90, 90B

Material: .125" aluminum, brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, and US32DMS (see page 9).

Fastener: Cylinder ring and self-adhesive mounting.

Options: No cylinder hole — screw mounted, order No. 90B.

No.	Size	Opening	Projection	Weight	ANSI A156.6
90	2" × 3¾"	1¼" dia.	1"	0.3 lbs.	J303
90B	2" × 3¾"	—	1"	0.3 lbs.	J303



Combination Push Pull Plates No. 91, 92, 93

Material: .125" aluminum, brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, and US32DMS (see page 9).

Fastener: #8 × ⅞" SMS.

Options:

- TORX - security Torx screws.
- Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes.

No.	Size	Projection	Weight	ANSI A156.6
91	3½" × 15¾"	1"	1.9 lbs.	J303
92	4" × 15¾"	1"	2.2 lbs.	J303
93	8" × 15¾"	1"	4.4 lbs.	J303



Flush Pulls No. 94, 94BTB

Material: .125" brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, US32D**MS**, US32D**316**, and US32**316** (see page 9).

NOTE: Cups are painted black on all finishes except stainless steel.

Fastener: No. 94: #8x $\frac{3}{4}$ " SMS.

No. 94BTB: #8 - 32x $\frac{3}{4}$ " OH MS with sleeves Type 10.

Options: TORX - security Torx screws.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
94	3 $\frac{1}{2}$ "x5"	1 $\frac{3}{4}$ "x3 $\frac{1}{8}$ "	$\frac{7}{8}$ "	0.6 lbs.	J403
94BTB (pair)	3 $\frac{1}{2}$ "x5"	1 $\frac{3}{4}$ "x3 $\frac{1}{8}$ "	1 $\frac{3}{4}$ "	1.2 lbs.	J403



Flush Pull No. 94C

Material: .125" brass, bronze, stainless steel.


Finishes: Available in standard architectural finishes, US32D**MS**, US32D**316**, and US32**316** (see page 9).

NOTE: Cups are painted black on all finishes except stainless steel.

Fastener: #6x1" TH SMS.

Features: Fasteners concealed in cup.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
94C	3 $\frac{1}{2}$ "x5"	1 $\frac{3}{4}$ "x3 $\frac{1}{8}$ "	$\frac{7}{8}$ "	0.6 lbs.	J403



Dead Lock Flush Pulls No. 94DLL, 94DLS

Material: .125" brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, US32D**MS**, US32D**316**, and US32**316** (see page 9).

NOTE: Cups are painted black on all finishes except stainless steel.

Fastener: #8x $\frac{3}{4}$ " OH SMS.

Features:

- Used with dead bolt lock. 1 $\frac{1}{4}$ " cylinder hole is standard.
- Vandal resistant.
- Use where projecting trim is an operational problem or an aesthetic objection.
- Ideal for use on "exit only" doors where occasional entrance is required (warehouse exits), night latch function exit device openings (classroom exit only doors), mechanical closet doors and anywhere dead locking is approved.

Options:

- TORX - security Torx screws.
- Custom sizes.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
94DLL	6 $\frac{1}{8}$ "x8"	1 $\frac{3}{4}$ "x6 $\frac{1}{8}$ "	$\frac{7}{8}$ "	1.0 lbs.	J403
94DLS	6 $\frac{1}{8}$ "x5"	1 $\frac{3}{4}$ "x3 $\frac{1}{8}$ "	$\frac{7}{8}$ "	0.8 lbs.	J403



Flush Pull No. 94L

- Material:** .125" brass, bronze, stainless steel.
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9).
NOTE: Cups are painted black on all finishes except stainless steel.
- Fastener:** ¼-20x 1½" thru bolt & finish washer (standard 1¾" door).
- Features:** Includes lugs for thru bolt. No fasteners on pull side.
- Options:**
- TORX - security Torx screws.
 - Advise if door thickness other than 1¾".


No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
94L	3½"x5"	1¾"x3⅝"	7⁄8"	0.6 lbs.	J403



Flush Pull No. 94P

- Material:** .125" brass, bronze, stainless steel.
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9).
NOTE: Cups are painted black on all finishes except stainless steel.
- Fastener:** ¼-20x 1½" MS.
- Features:** Usually used with the 94L as a set (see below).
- Options:** TORX - security Torx screws.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
94P	3½"x5"	1¾"x3⅝"	7⁄8"	0.6 lbs.	J403



Flush Pull Set No. 94P x 94L

- Material:** .125" brass, bronze, stainless steel.
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9).
NOTE: Cups are painted black on all finishes except stainless steel.
- Fastener:** ¼ - 20 x 1½" thru bolt (standard 1¾" door).
- Options:**
- TORX - security Torx screws.
 - Advise if door thickness other than 1¾".

No.	Size	Weight	ANSI A156.6
94P x 94L	Set consists of 1 94L and 1 94P	1.3 lbs.	J403



Flush Pull No. 95A

- Material:** Cast brass.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** #6 x 5/8" SMS.
- Features:** Fasteners concealed in cup.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
95A	2 3/16" x 3 1/4"	7/8" x 2 7/16"	3/4"	0.6 lbs.	J403



Flush Pull No. 95B

- Material:** Cast brass.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** #8 x 7/8" SMS.
- Features:** Fasteners concealed in cup.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
95B	2 11/16" x 4 3/16"	1 7/16" x 3 1/2"	3/4"	0.8 lbs.	J403



Flush Pull No. 95R

- Material:** Cast brass.
- Finishes:** Available in standard architectural finishes (see page 9).
- Fastener:** #8 x 7/8" SMS.
- Features:** Fasteners concealed in cup.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
95R	3 1/2" dia.	2 3/4" x 1 11/16"	7/8"	0.6 lbs.	J403



Flush Pull No. 96

Material: .125" aluminum, brass, bronze, stainless steel.


Finishes: Available in standard architectural finishes (see page 9).

Fastener: #8x $\frac{7}{8}$ " SMS.

Options:

- TORX - security Torx screws.
- Special sizes.
- Cylinder cutouts (CFC) and turn knob cutouts (CTFF). See page B1 for standard locations and sizes.

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
96	4" x 16"	1 $\frac{3}{4}$ " x 3 $\frac{1}{8}$ "	$\frac{7}{8}$ "	2.2 lbs.	J403



No. BF97

Barrier Free Flush Pulls No. BF97, BF97L

Material: .125" brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, and US32DMS (see page 9).

Fastener: No. BF97: #8x $\frac{7}{8}$ " SMS.

No. BF97L: #10-24 stud welded lugs and #10-24 thru bolts.

Options: TORX - security Torx screws.

Features: ADA flush pull.



No. BF97L

No.	Size	Grip Opening	Depth	Weight	ANSI A156.6
BF97	5" x 5"	2 $\frac{1}{2}$ " x 3 $\frac{1}{2}$ "	$\frac{7}{8}$ "	1.0 lbs.	J403
BF97L	5" x 5"	2 $\frac{1}{2}$ " x 3 $\frac{1}{2}$ "	$\frac{7}{8}$ "	1.0 lbs.	J403