

BF Series ADA Signs

- Material:** .125" non-glare plastic or .050" brass, bronze.
- Finishes:** Plastic signs: available in black, blue, brown, or red with standard 1" white lettering.
Metal signs: available in standard architectural finishes (see page 9).
- Fastener:** 4 ea. #6x $\frac{5}{8}$ " OH SMS.
- Size:** 8"x8".
- Ordering:** Specify background finish along with any options.
- Features:** Plastic signs:
 - Raised characters and Grade 2 Braille translation.
 - Meets ADAAG Section 4.30 requirements.Metal signs:
 - Raised black lettering and Grade 2 Braille translation.
 - Attractive architectural finishes.
- Options:** • SA - self-adhesive mounting.

No. BF683



No. BF684



No. BF685



No. BF686



No. BF687



No. BF688



No. BF689



Recommended Mounting Location for Signs

Excerpts from ADA Accessibility Guidelines for Buildings and Facilities (ADAAG).

4.30.6 Mounting Location and Height: Where permanent identification is provided for rooms and spaces, signs shall be installed on the wall adjacent to the latch side of the door. Where there is no wall space to the latch side of the door, including at double leaf doors, signs shall be placed on the nearest adjacent wall. Mounting height shall be 60" (1525 mm) above the finish floor to the centerline of the sign. Mounting location for such signage shall be so that a person may approach within 3" (76 mm) of signage without encountering protruding objects or standing within the swing of a door.

