

800-458-2424 www.rockwoodmfg.com



## Low Dome Stops No. 440, 441

Material: Solid cast brass with DuraFlex bumper.

Finishes: Available in standard architectural finishes (see page 9). Other: No. 441 is packed with both WS and MS fasteners. For doors without thresholds (not undercut). Features:

Options: Exterior pack screw packs, stainless steel plated to match — use EXP suffix

 $(440 \times EXP)$  when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
440	#12×11/4" FH WS, plastic anchor	1/4" h × 11/8" dia.	11/8"	2.1 lbs./10	L02141
441	#12×1½" FH WS, plastic anchor; #12-24 × 1" FH MS, lead anchor	1/4"h×17/8"dia.	11/8"	2.5 lbs./10	L02141



### Dome Stop Combination Unit No. 441CU

Material: Solid cast brass with DuraFlex bumper.

Finishes: Available in standard architectural finishes (see page 9).

Set consists of 1 each No. 441 and 1 each No. 444. For use at doors with Other:

or without a threshold.

Convertible for undercut or not undercut doors. Features:

Options: Exterior pack screw packs, stainless steel plated to match — use EXP suffix

(441CUxEXP) when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
441CU		Dome stop: ¼"h×1½" dia. Riser: ¾"h×2" dia.	11/8" or 11/2"	3 lbs./10	L02141/ L02161
444	Cast riser only	¾"h × 1½" dia.	3/8"	10 ozs./10	L02141



#### Cast Universal Dome Stop No. 441H

Material: Solid cast brass with DuraFlex bumper.

Available in standard architectural finishes (see page 9). Finishes:

Low lip dome stop with height of high dome stop, eliminates the need to Features: determine requirement for traditional low or high dome stop - one stop

for all applications. Integral cast pin for added strength. Universal screw

pack included for all floor conditions.

Exterior pack screw packs, stainless steel plated to match — use EXP suffix Options:

(441H×EXP) when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
44 <b>1</b> H	#12×11/4" FH WS, plastic anchor	⅓2"h×1%" dia.	111/16"	3.2 lbs./10	L02141
	#12-24×1" FH MS, lead anchor				L02161



## High Dome Stops No. 442, 443

Material: Solid cast brass with DuraFlex bumper.

Finishes: Available in standard architectural finishes (see page 9). No. 443 is packed with both WS and MS fasteners. Other: For doors with thresholds or undercut doors. Features:

Options: Exterior pack screw packs, stainless steel plated to match — use EXP suffix  $(442 \times EXP)$  when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
442	#12×1½" FH WS, plastic anchor	½"h×1%" dia.	1½"	2.8 lbs./10	L02161
443	#12×1½" FH WS, plastic anchor; #12-24 × 1" FH MS, lead anchor	½"h×1%" dia.	1½"	3.2 lbs./10	L02161



# Door Stop Riser No. 449

Material: Aluminum.

Mill aluminum or painted to match. Finishes:

Ordering: Specify finish and thickness; 1/4", 3/8", 1/2", 5/8", 3/4", 1".

Full size carpet riser provides sturdy base for mounting the No. 440 or Other: No. 442 dome stop.

No.	Fastener	Base	Height	Weight
449	#12 WS, plastic anchor	1%" dia.	As specified	1.6 lbs./10



Fastener

No. 445H

No.

## Heavy Duty Door Stop No. 445, 445H

Solid cast brass with DuraFlex bumper. Material: Finishes:

Available in standard architectural finishes (see page 9). Extra heavy duty dome type stop for heavy and high frequency doors. Features:

Exterior pack screw packs, stainless steel plated to match — use EXP suffix Options:  $(445 \times EXP)$  when ordering.

Base

445	2 ea. #12×1½" FH SMS, plastic anchor; #12-24×1" FH MS, lead anchor 2"×4"	11/8"	5.5 lbs./10
445H	2 ea. #12×1½" FH SMS, plastic anchor; #12-24×1" FH MS, lead anchor 2"×4"	111/16"	5.5 lbs./10



Door Stop No. 446

Available in standard architectural finishes (see page 9). Finishes:

Brass with DuraFlex bumper. Material:

Features: Modern style universal stop. Options:

DuraFlex bumper available in standard gray or optional black.

INO.	rastener	Base	Height	vveignt
446	#12×1½" WS, plastic anchor; #12-24×1" FH MS, lead anchor	11/4"	1½"	0.5 lbs.

in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.

in door opening solutions

Weight

Height