



Door Stops No. 480, 481

- Material:** Solid cast brass with DuraFlex bumper.
- Finishes:** Available in standard architectural finishes (see page 9).
- Features:**
- Uses replacement bumper 461B.
  - Heavy duty and ideal for use on heavy doors or in high traffic areas.
- Options:**
- DuraFlex Bumper available in standard gray or optional black.
  - Exterior pack screw packs, stainless steel plated to match — use EXP suffix (480 x EXP) when ordering.

No.	Fastener	Base	Height	Weight
480	3 ea. #12×1¼" FH WS, 3 ea. plastic anchors	2½"×1¾"	1⅝"	5.8 lbs./10
481	3 ea. #12-24×1" FH MS, 3 ea. lead anchors	2½"×1¾"	1⅝"	5.8 lbs./10



Door Stops No. 480H, 481H

- Material:** Solid cast brass with DuraFlex bumper.
- Finishes:** Available in standard architectural finishes (see page 9).
- Features:**
- Uses replacement bumper 461B.
  - Heavy duty and ideal for use on heavy doors or in high traffic areas.
- Options:**
- DuraFlex bumper available in standard gray or optional black.
  - Exterior pack screw packs, stainless steel plated to match — use EXP suffix (480HxEXP) when ordering.

No.	Fastener	Base	Height	Weight
480H	3 ea. #12×1¼" FH WS, 3 ea. plastic anchors	2½"×1¾"	2¼"	6.2 lbs./10
481H	3 ea. #12-24×1" FH MS, 3 ea. lead anchors	2½"×1¾"	2¼"	6.2 lbs./10



Heavy Duty Mounting Plate No. 481MP

- Material:** Aluminum and steel.
- Finishes:** Powder coat to match stop finish.
- Features:** ⅜" aluminum base plate for securely anchoring 481 or 481H door stops in heavy use areas.
- Installation:** Requires 3½" diameter hole 3½" deep. Fill with quick drying cement and set anchor plate flush to finished floor with hole pattern at appropriate location for door stop to interface with door surface.

No.	Fastener	Base	Height	Weight
481MP	None	3" dia	Flush to floor	4.5 lbs./10



Door Stop No. 482

- Material:** Solid cast brass with DuraFlex bumper.
- Finishes:** Available in standard architectural finishes (see page 9).
- Features:**
- Uses replacement bumper 461B.
  - Heavy duty and ideal for use on heavy doors or in high traffic areas.
- Options:**
- DuraFlex bumper available in standard gray or optional black.
  - Exterior pack screw packs, stainless steel plated to match — use EXP suffix (482 x EXP) when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
482	⅝"-18×1¾" stud, lead anchor; #12×1¼" FH WS, plastic anchor	1½"×2½"	2⅝"	6.5 lbs./10	L02131



Door Stop No. 483

- Material:** Solid cast brass with DuraFlex bumper.
- Finishes:** Available in standard architectural finishes (see page 9).
- Features:**
- Uses replacement bumper 461B.
  - Heavy duty and ideal for use on heavy doors or in high traffic areas.
- Options:**
- DuraFlex Bumper available in standard gray or optional black.
  - Exterior pack screw packs, stainless steel plated to match — use EXP suffix (483 x EXP) when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
483	⅝"-18×1¾" stud, lead anchor; #12×1¼" FH WS, plastic anchor	1⅝"×2⅝"	2¾"	6.7 lbs./10	L02131



Door Stop with Keeper No. 485

- Material:** Solid cast brass with DuraFlex bumper.
- Finishes:** Available in standard architectural finishes (see page 9).
- Features:**
- Uses replacement bumper 461B.
  - Heavy duty and ideal for use on heavy doors or in high traffic areas.
- Options:**
- DuraFlex Bumper available in standard gray or optional black.
  - Exterior pack screw packs, stainless steel plated to match — use EXP suffix (485 x EXP) when ordering.

No.	Fastener	Base	Height	Weight	ANSI A156.16
485	⅝"-18×1¾" stud, lead anchor; #12×1¼" FH WS, plastic anchor	1⅝"×2⅝"	3"	7.8 lbs./10	L01371
	Keeper: 2 ea. #10×1" FH SMS	1"×2"			