



Pull Plates No. 102 x 70, 105 x 70, 106 x 70, 107 x 70

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in any finish, US32DMS and US32D316 (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Barrier Free available in 2 1/2" clearance — use BF prefix when ordering (BF102 x 70C)
 - Advise if door thickness is other than 1 3/4"
 - See page B13 for mounting selection (standard duty 1/4" - 20)

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
102 x 70B	5/8" dia.	5 1/2"	70	3 1/2" x 15"	1.8 lbs.	J405
102 x 70C	5/8" dia.	5 1/2"	70	4" x 16"	1.9 lbs.	J405
105 x 70B	3/4" dia.	5 1/2"	70	3 1/2" x 15"	2.1 lbs.	J405
105 x 70C	3/4" dia.	5 1/2"	70	4" x 16"	2.2 lbs.	J405
106 x 70B	3/4" dia.	6"	70	3 1/2" x 15"	2.2 lbs.	J405
106 x 70C	3/4" dia.	6"	70	4" x 16"	2.3 lbs.	J405
107 x 70B	3/4" dia.	8"	70	3 1/2" x 15"	2.4 lbs.	J405
107 x 70C	3/4" dia.	8"	70	4" x 16"	2.5 lbs.	J405



Pull Plates No. 110 x 70, 111 x 70

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in any finish, US32DMS and US32D316 (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Barrier Free available in 2 1/2" clearance — use BF prefix when ordering (BF110 x 70C)
 - Advise if door thickness is other than 1 3/4"
 - See page B13 for mounting selection (standard duty 1/4" - 20)
 - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
110 x 70B	1" dia.	8"	70	3 1/2" x 15"	3.8 lbs.	J405
110 x 70C	1" dia.	8"	70	4" x 16"	3.9 lbs.	J405
111 x 70B	1" dia.	10"	70	3 1/2" x 15"	4.3 lbs.	J405
111 x 70C	1" dia.	10"	70	4" x 16"	4.4 lbs.	J405



Pull Plates No. 122 x 70, 123 x 70

- Material:** Aluminum, brass, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in any finish (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
 - See page B13 for mounting selection (standard duty 1/4-20)
 - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
122 x 70B	3/8" x 1 1/4"	6"	70	3 1/2" x 15"	2.2 lbs.	J405
122 x 70C	3/8" x 1 1/4"	6"	70	4" x 16"	2.3 lbs.	J405
123 x 70B	3/8" x 1 1/4"	8"	70	3 1/2" x 15"	2.5 lbs.	J405
123 x 70C	3/8" x 1 1/4"	8"	70	4" x 16"	2.6 lbs.	J405



Pull Plates No. 125 x 70, 126 x 70

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in any finish (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
 - See page B13 for mounting selection (standard duty 1/4-20)
 - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
125 x 70B	1" half round	6"	70	3 1/2" x 15"	2.0 lbs.	J405
125 x 70C	1" half round	6"	70	4" x 16"	2.1 lbs.	J405
126 x 70B	1" half round	8"	70	3 1/2" x 15"	2.3 lbs.	J405
126 x 70C	1" half round	8"	70	4" x 16"	2.4 lbs.	J405



Pull Plates No. 132 x 70

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in any finish, and US32DMS (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
 - See page B13 for mounting selection (standard duty 1/4" - 20)
 - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
132 x 70B	Cast	5 1/2"	70	3 1/2" x 15"	1.7 lbs.	J405
132 x 70C	Cast	5 1/2"	70	4" x 16"	1.8 lbs.	J405



Pull Plates No. 137 x 70

- Material:** Brass, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in any finish (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
 - See page B13 for mounting selection (standard duty 1/4" - 20)
 - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
137 x 70B	Cast	5 1/2"	70	3 1/2" x 15"	1.7 lbs.	J405
137 x 70C	Cast	5 1/2"	70	4" x 16"	1.8 lbs.	J405



No. 147 x 76B



No. 147 x 77B

Pull Plates No. 147 x 76, 147 x 77

Material: Cast brass.

Finishes: Available in standard architectural finishes (see page 9)

Fastener: #6 x ⁵/₈" OH SMS; ¹/₄" - 20 x 2 ¹/₄" thru bolt & finish washer (standard 1 ³/₄" door)

Options:

- Advise if door thickness is other than 1 ³/₄"
- See page B13 for mounting selection (standard duty ¹/₄" - 20)

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
147 x 76B	Cast	6"	76	3 ¹ / ₂ " x 15"	2.1 lbs.	J405
147 x 76C	Cast	6"	76	4" x 16"	2.2 lbs.	J405
147 x 77B	Cast	6"	77	3 ¹ / ₂ " x 15"	2.1 lbs.	J405
147 x 77C	Cast	6"	77	4" x 16"	2.2 lbs.	J405



No. 148 x 76B



No. 148 x 77B

Pull Plates No. 148 x 76, 148 x 77

Material: Cast brass

Finishes: Available in standard architectural finishes (see page 9)

Fastener: #6 x ⁵/₈" OH SMS; ¹/₄" - 20 x 2 ¹/₄" thru bolt & finish washer (standard 1 ³/₄" door)

Options:

- Advise if door thickness is other than 1 ³/₄"
- See page B13 for mounting selection (standard duty ¹/₄" - 20)

No.	Pull	CTC	Plate	Size	Weight	ANSI A156.6
148 x 76B	Cast	8"	76	3 ¹ / ₂ " x 15"	2.7 lbs.	J405
148 x 76C	Cast	8"	76	4" x 16"	2.8 lbs.	J405
148 x 77B	Cast	8"	77	3 ¹ / ₂ " x 15"	2.7 lbs.	J405
148 x 77C	Cast	8"	77	4" x 16"	2.8 lbs.	J405

ASSA ABLOY
Opening Solutions

Experience a safer
and more open world

800-458-2424 | www.assaabloydooraccessories.us
Check the web site for the up-to-date catalog


Copyright © 2012-2019, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

NOTE: Y base plates are recommended on wood or glass doors to make a stable and durable mounting.

NOTE: Heavy Duty (HD/XHD) mounting features hex drive for positive tightening and large overall size for superior strength. Recommended for high frequency and rough service openings.


Thru Bolt

Wood or Metal Door - Type 1




Type	Bolt Size	Drill Size	
		Wood	Metal
1	1/4 - 20	9/32	9/32
1HD	5/16 - 18	11/32	11/32
1XHD	3/8 - 16	13/32	13/32

Wood or Metal Door - Type 12



Type	Bolt Size	Drill Size	
		Wood	Metal
12	1/4 - 20	9/32	9/32
12HD	5/16 - 18	11/32	11/32
12XHD	3/8 - 16	13/32	13/32


Glass Door - Type 15



Type	Bolt Size	Drill Size	
		Glass	
15	1/4 - 20	5/8	
15HD	5/16 - 18	5/8	
15XHD	3/8 - 16	5/8	


Back to Back

Wood or Metal Door - Type 16



Type	Bolt Size	Drill Size	
		Wood	Metal
16	1/4 - 20	9/32	9/32
16HD	5/16 - 18	11/32	11/32


Glass Door - Type 18



Type	Bolt Size	Drill Size	
		Glass	
18	1/4 - 20	5/8	
18HD	5/16 - 18	5/8	


Concealed

Metal Door - Type 17



Type	Bolt Size	Drill Size	
		Metal	
17	1/4 - 20	1/4 - 20 tap	
17HD	5/16 - 18	5/16 - 18 tap	

Metal Door - Type 17R



Type	Bolt Size	Drill Size	
		Metal	
17R	1/4 - 20	N/A	