

45° Offset Door Pulls No. BF160, BF161, BF162

Material: Aluminum, brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, US32DMS, US32D316, US32316,

white (WPC), red (RPC), and black (BPC) powder coat finishes

(see page 9).

Fastener: $\frac{1}{4}$ - 20 × 2 $\frac{1}{4}$ " thru bolt & finish washer (standard $\frac{1}{4}$ " door).

Options: • Back to back mounting in pairs — use BTB suffix and mounting type

number (BF160BTB16).

Concealed mounting single pulls — use C suffix and mounting type

number (BF160C17).

• Advise if door thickness is other than 13/4".

 \bullet See page B27 for mounting selection (standard duty 1/4 - 20).

 Use Y prefix (YBF160) when ordering pulls with base plates, Y plate diameter is 1½; recommended for use on wood and glass doors.

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight	ANSI A156.6
BF 1 60	¾" dia.	8"	83/4"	3/4"	31/4"	2½"	3"	1.8 lbs.	J402
BF161	¾" dia.	10"	10¾"	3/4"	31/4"	2½"	3"	2.0 lbs.	J402
BF162	¾" dia.	12"	12¾"	3/4"	31/4"	2½"	3"	2.2 lbs.	J402



No. BF166, BF167A, BF167, BF168, BF169

Material: Aluminum, brass, bronze, stainless steel.

Finishes: Available in standard architectural finishes, US32DMS, US32D316, US32316,

white (WPC), red (RPC), and black (BPC) powder coat finishes

(see page 9).

Fastener: 1/4 - 20 x 21/4" thru bolt & finish washer (standard 13/4" door).

Options:

 Back to back mounting in pairs — use BTB suffix and mounting type number (BF166BTB16).

Concealed mounting single pulls — use C suffix and mounting type

number (BF166C17).

• Advise if door thickness is other than 1¾".

 Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF166BTB16HD).

• See page B27 for mounting selection (standard duty 1/4 - 20).

 Use Y prefix (YBF16) when ordering pulls with base plates, Y plate diameter is 1¼"; recommended for use on wood and glass doors.

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight	ANSI A156.6
BF 1 66	1 " dia.	8"	9"	1"	3½"	21/2"	3"	2.8 lbs.	J402
BF167A	1 " dia.	9"	10"	1"	3½"	21/2"	3"	3.0 lbs.	J402
BF 1 67	1 " dia.	10"	11"	1"	3½"	21/2"	3"	3.2 lbs.	J402
BF 1 68	1 " dia.	12"	13"	1"	3½"	21/2"	3"	3.6 lbs.	J402
BF 1 69	1 " dia.	18"	19"	1"	3½"	2½"	3"	5.0 lbs.	J402

