
















Cams for Schlage Mortise Cylinders in Other Manufacturers' Mortise Locks

	Modular Cylinder Cyl. length 1 1/8", 1 3/8", 1 5/8"	Modular Cylinder Cyl. length 1 1/4", 1 1/2", 1 3/4"	Classic Conventional Non-IC 20-001	Interchangeable Core 20-061, 20-771, 26-094, 80-102, 80-110, 80-132, 80-302	Everest 29 & Primus Non-IC 20-001 Everest 29 Conventional 20-500 and 20-700 Primus
Corbin Russwin® DL4000 Series (Old Corbin 420 and Russwin 1503)	B520-730  Dim. X = .153 Y = .761	B520-731  Dim. X = .153 Y = .761	B520-295  Dim. X = .155 Y = .775	B520-254 (was XB11-426) 	B520-366 (was XB11-656) 
Corbin Russwin® ML2200 Series (Old Corbin 7000-9000 and Russwin 4000-5000) All functions except ML2255 and ML2242 inside (see straight cam)	B520-732  Dim. X = .236 Y = .731	B520-733  Dim. X = .236 Y = .731	B520-233 (was XB08-899)  Dim. X = .232 Y = .729	B520-253 (was XB11-352) 	B520-309 (was XB11-629) 
Corbin Russwin A65 ML2200 master ring deadbolt functions manufactured before 6/10/93 and old Russwin cast iron residential locks. For all Best 40H Series & 30H Deadbolt function	B520-734  Dim. X = .242 Y = .757	B520-735  Dim. X = .242 Y = .757	B520-223 (was XB03-142)  Dim. X = .235 Y = .729	B520-360 (was XB11-817) 	B520-367 (was XB11-887) 
Yale® 2160 Arrow® #004 Sargent® 13-0660 All functions except 16 inside and 50 outside	B520-736  Dim. X = .187 Y = .727	B520-737  Dim. X = .187 Y = .727	B520-256 (was XB11-430, replaces XB10-659)  Dim. X = .186 Y = .718	B520-296 (was XB11-461, replaces XB11-484) 	B520-329 (was XB11-631, replaces XB11-630) 
Best 30 Latch Function	L583-476  Dim. X = .35 Y = .72	L583-477  Dim. X = .35 Y = .72	B502-191 Classic Conventional  Dim. X = .338 Y = .71	K510-730  Dim. X = .338 Y = .71	B502-948 Everest 29 & Primus  Dim. X = .338 Y = .71

The following complete cylinders are available. Specify the desired cam from the correct column above:

Cylinder Mechanism

Conventional cylinder
Primus XP cylinder
Primus XP UL437 Listed cylinder
Full size IC with conventional core
Full size IC with Primus XP core
Full size IC housing less core
SFIC with Everest 29 core
SFIC with keyed construction core
SFIC with disposable construction core
SFIC housing less core

Collar

compression ring and spring
compression ring and spring
compression ring and spring
compression ring, spring, 3/8" blocking ring
compression ring, spring, 3/8" blocking ring
compression ring, spring, 3/8" blocking ring
compression ring, spring, 1/4" blocking ring
compression ring, spring, 1/4" blocking ring
compression ring, spring, 1/4" blocking ring
compression ring, spring, 1/4" blocking ring

How to Order

20-001 x cam number
20-700 x cam number
20-500 x cam number
20-061 x cam number
20-771 x cam number
26-094 x cam number
80-302 x cam number
80-132 x cam number
80-110 x cam number
80-102 x cam number