

Electrically-released lockset with multi-point deadbolt security which locks out access control.

Application:

- Areas of refuge
- Inventory Rooms
- Offices

Function Description:

Daytime latch lock operation with electric release. Entry by key or electric release at all times.

Projection of deadbolts from interior by turnpiece or exterior by key disables electric release. Entry by key only during this time.

Features:

- Multi-point deadbolts may be projected at any time via interior turnpiece or exterior key.
- Full life-safety compliance at all times with single motion exiting.
- Access control interface allows entry (24vDC required).
- Bolt position switch provided for tie-in to access control system (end-of-day locking signal).
- Access control system is disabled when the deadbolts are projected. Key required for entry.
- This model does not include a request-to-exit signal.


74L-AP-L3E (Full #: 74L46-GK3E-CVR-HVL-BPS2-LRS-CW-F97G-630)

Model #	Description
74L	Multi-Bolt Mortise Lock 4-Point lever by lever lock Bolts extend manually, door latches each time it closes
46-GK3E	Exterior lever always locked, Single opening by key or 24VDC electric release. GE3 trim style, tubular lever with return. Key exterior or thumb turn interior to extend deadbolts.
CVR-HVL	Concealed vertical bolts with HVL lower bolt module
BPS2-LRS	Double bolt position switch - 1st switch signals store alarm that bolts are not extended. 2nd switch causes the lever electric release to be disengaged when the bolts are extended by key or thumb turn.
CW	Concealed wiring – power must be brought onto door.
F97G	Wiring Harness to connect device parts.
630	Stainless steel finish

**New Stainless Steel
Lever Trim***



- Full stainless steel construction
- 6 thru-bolts
- New vertical spring orientation



* Cylinder ordered separately

Optional Exterior
Cylinder:
TEL-RC1
Removable core
mortise cylinder
with construction
core

Recommended
Power Supply:
PS-D111
24VDC,
Fail-Secure
operation, dry
contact input

Recommended
Power Transfer:
EH4545-626-4
Electrified Hinge 4½
x 4½"
4 wire



Older style
trim shown
in photos



Order Separately

Required:

**Mortise
Cylinder**



Please note cam
requirement



*Straight
"Yale"
type*

*May be provided by access control
system or hardware supplier:*

Power Supply



Electrified Hinge



*Or other power
transfer method*

c:\vmb_x1c_files\xt_docs\technical\ - mmi_model number info\MMI 74L-AP-L3 E v2a.vsd\page-1.vas of 4/4/20