

Markar HG311 Swing Clear Hinge Guard

Standard Features

Barrel Type Hinge
 .187" diameter Stainless Steel pin (rod)
 Medical bearings
 Stainless Steel end pins
Material
 Heavy-duty 14 gauge Stainless Steel
Finishes
 US32D Satin Stainless Steel (630)
Standards
 ANSI/BHMA Standard A156.26 Grade 1
Mounting Hardware
 Fasteners concealed when door is closed
 Custom 12-24 x $1\frac{1}{16}$ " S.S Phillips Flat Head Undercut TEK Screws

Capacity
 Supports weights up to 600 lbs.
 4'0" maximum door width
Standard Sizes
 6'8", 7'0", 7'2", 8'0", 10'0"
Hole Pattern
 Symmetrically templated
Handing
 Not required for standard 7'0", 8'0" or 10'0". Specify handing for 6'8" and 7'2" and for most optional features
Door Edge
 Square hinge edge
 For beveled hinge edge use HG310

Fire Rating
 3 hours- hollow metal doors
 90 minutes- hollow metal and composite core wood fire doors
 20 minutes- wood doors



Classified in accordance with UL10C for positive pressure




Fire-rated label

Optional Features

Finishes
 US32 Bright Stainless Steel (629)
 Scratch-Resistant Powder Coated Paint
Fasteners
 Tamper-proof security screws

Other Features
 Custom lengths- specify in inches
 Custom hole pattern
 Dutch door hinges - suffix "DDP"
 Hospital tips - suffix "HT"
 Welded End Pins

Tools
 MTSP-100 Right angle skewdriver for ease of installation



Electrical Modifications
 Current Transfer Prep (door leaf only) - suffix "CTP"
 (EL-EPT-SC Power Transfer Recommended)

This surface applied swing clear version allows doors to meet ADA requirements. The single wrap protects door edges from cart damage.

