McKINNEY Hinge Catalog Full Mortise Plain Bearing Hinges Five Knuckle Standard Weight Series



T2314

Stainless steel base or available in brass or bronze base material polished and plated or furnished in powder coat.

T2714


Steel base polished and plated or furnished in powder coat finish.



Available Options:

- NRP (non-removable pin)
- RC (round corner ¹/₄" radius furnished unless specified otherwise)
- HT (hospital tip)
- BT (ball tip)
- ST (steeple tip)
- SSF (safety stud feature)
- Beveled Edge (where doors are beveled on hinge side specify T4314 or T4714)

APPLICATION



Available Sizes			
Inches	MM	Gauge	
3½ x 3½	88.9 x 88.9	.123	
4 x 4	101.6 x 101.6	.130	
4½ x 4	114.3 x 101.6	.134	
4½ x 4½	114.3 x 114.3	.134	
5 x 4½	127 x 114.3	.146	
5 x 5	127 x 127	.146	
6 x 6*	152.4 x 152.4	.160	

*Not available in Stainless

Full Mortise Hinge Fasteners			
Hinge Size	Machine	Wood	
3½ x 3½	½ x 10-24	1 x 10	
4 x 4	½ x 12-24	1¼ x 12	
4½ x 4	½ x 12-24	1¼ x 12	
4½ x 4½	½ x 12-24	1¼ x 12	
5 x 4½	½ x 12-24	1¼ x 12	
5 x 5	½ x 12-24	1¼ x 12	
6 x 6	½ x ¼-24	1¼ x 14	

Packing:

All standard weight full mortise hinges are packed with all machine x all wood screws. For special screws consult price book on availability.

ANSI Cross Reference:

A2133 Brass, Bronze A5133 Stainless A8133 Steel

Not recommended for medium or high frequency doors, or doors with closing devices.