

## Jamb Mount Pivot Set

Recommended for installations on average frequency double acting doors in schools, hospitals, institutions and other public buildings.

- Used in conjunction with CSS-9 Combinations Strike and Stops and DS-6 Emergency Door Stops
- Thrust steel ball bearing in bottom pivot, oil impregnated bronze bearing in top pivot
- Center Hung
- Mortised into side jamb
- Full mortise top pivot
- Non-handed
- 1<sup>5</sup>/<sub>32</sub> radius heel edge of door
- Maximum Door Weight (interior or exterior) up to 125 lbs 3'6" x 8'0"
- All EP-5J Pivot sets are packed with 14 x 1<sup>1</sup>/<sub>2</sub>" wood screws and 1/4"-20 x 5/8" machine screws
- Ferrous base pivot set polished and plated

EP-5J



### Specifications

No.	ANSI Cross Reference	Base Material
EP-5J	C07042	Steel

### Door Weight Chart

(lbs per square foot)

	Door Thickness	
	1 <sup>3</sup> / <sub>4</sub> "	2"
Aluminum	3 <sup>1</sup> / <sub>2</sub> lbs	5 lbs
Wood-Particle Core	5 lbs	5 <sup>3</sup> / <sub>4</sub> lbs
Wood-Stave Block Core	4 lbs	4 <sup>1</sup> / <sub>2</sub> lbs
14 Gauge Hollow Metal	8 <sup>3</sup> / <sub>4</sub> lbs	10 lbs
16 Gauge Hollow Metal	7 <sup>1</sup> / <sub>2</sub> lbs	8 <sup>1</sup> / <sub>2</sub> lbs
18 Gauge Hollow Metal	6 <sup>1</sup> / <sub>2</sub> lbs	7 <sup>1</sup> / <sub>2</sub> lbs

800-346-7707 | [www.mckinneyhinge.com](http://www.mckinneyhinge.com)

Check the web site for the up-to-date catalog

McKinney is a brand associated with Corbin Russwin, Inc., an ASSA ABLOY Group company. Copyright © 2012-2017, Corbin Russwin, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of Corbin Russwin, Inc. is prohibited.

## ASSA ABLOY

The global leader in door opening solutions

RH-1