Interchangeable Core

► 725MD Mortise Deadbolt

BEST

For BEST style interchangeable core cylinders

725MD3DWKVH

Mortise Mounted



725MD 725MD-DW-VH



725MD-DR-LH




725MD-DR-RH

			en.
- 4	-	◥	IA.
a		4	ID.
- 4			IF.

725MD-DW-IH


Item	Function	Finish	Cyl. Length	Description	
725MD-DR-RH	RH Door	26D, US26, US3, US4, 10B	1-1/16"	Lock body - For small format IC	
725MD3DR-RH	RH Door	26D	1-3/8"		
725MD-DR-LH	LH Door	26D, US26, US3, US4, 10B	1-1/16"		
725MD3DR-LH	LH Door	26D	1-3/8"		
725MD-DW-VH	VH Drawer	26D, US26, US3, US4, 10B	1-1/16"		
725MD3DW-VH	VH Drawer	26D	1-3/8"		
725MD-DW-IH	IH Drawer	26D, US26, US3, US4, 10B	1-1/16"		
725MD3DW-IH	IH Drawer	26D	1-3/8"		
Below locks are "key-retaining" (key removable in locked position only)					
725MD-DWKVH	VH Drawer	26D, US26, US3, US4, 10B	1-1/16"	Lock body -	

1-3/8"



VH Drawer

26D



For small format IC

725MD

(Mortise Deadbolt) Standard configuration. Dimensions are the same for all handings.

Best Compatible (Small Format)

SPECIFICATIONS

Retrofits: Best 5L7MD Mounting: Mortise

ANSI/BHMA: Passed ANSI/BHMA A156.11 Grade 1

performance requirements

Material: Zinc die cast cylinder housing, steel back

plate and steel case

Cylinder length: 1-1/16" or 1-3/8"

Barrel diameter: 1-1/8"

Key-retaining: Available for DW-VH applications Finish: US26, 26D, US3, US4 or 10B (1-3/8" barrel length locks available in 26D finish only)

Packaged: Packed 10 per box

KEYING INFORMATION

Cores: Not included

Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen

XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

725-1 spacer to fit 6 or 7 pin cores 725-SP-MD slotted rectangular strike 725-PA plastic thumbturn

OPTIONAL ACCESSORIES

See the accessories section of this catalog for a complete list.

Spacers: WP725 (1/8" thick), WP726 (1/4" thick)

Strikes: 725-SP Series

SFIC cores: 206/207 Series (page 60)

