Interchangeable Core

► **725RD** Rim Deadbolt

BEST

For BEST style interchangeable core cylinders

725RD3DWKVH

Surface Mounted



725RD 725RD-DW-VH



725RD-DR-LH



725RD-DR-RH

1-3/8"


	0 0	N
•	8	6

725RD-DW-IH

Item	Function	Finish	Cyl. Length	Description
725RD-DR-RH	RH Door	26D, US26, US3, US4, 10B	1-1/16"	Lock body - For small format IC
725RD3DR-RH	RH Door	26D	1-3/8"	
725RD-DR-LH	LH Door	26D, US26, US3, US4, 10B	1-1/16"	
725RD3DR-LH	LH Door	26D	1-3/8"	
725RD-DW-VH	VH Drawer	26D, US26, US3, US4, 10B	1-1/16"	
725RD3DWVH	VH Drawer	26D	1-3/8"	
725RD-DW-IH	IH Drawer	26D, US26, US3, US4, 10B	1-1/16"	
725RD3DW-IH	IH Drawer	26D	1-3/8"	
Below locks are with "key-retaining" function (key removable in locked position only)				
725RD-DWKVH	VH Drawer	26D, US26, US3, US4, 10B	1-1/16"	Lock body -

3/4" | 1 5/8" | 2 3/16" | 2 3/16" | 2 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" | 3 3/16" |

VH Drawer



Lock body -For small format IC

725RD

(Rim Deadbolt) Standard configuration. Dimensions are the same for all handings.

Best Compatible (Small Format)

SPECIFICATIONS

Retrofits: Best 5L7RD Mounting: Rim (surface)

ANSI/BHMA: Passed ANSI/BHMA A156.11 Grade 1

performance requirements

Material: Zinc die cast cylinder housing, steel back

plate and steel case

Cylinder length: 1-1/16" or 1-3/8"

Barrel diameter: 1-1/8"

Key-retaining: Available for DW-VH applications Finish: US26, 26D, US3, US4 or 10B (1-3/8" barrel length locks available in 26D finish only)

Packaged: Packed 10 per box

KEYING INFORMATION:

Cores: Not included.

Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

725-1 spacer to fit 6 or 7 pin cores 725-SP-RD solid rectangular strike 725-PA plastic thumbturn

OPTIONAL ACCESSORIES

See the accessories section of this catalog for a complete list.

Spacers: WP725 (1/8" thick), WP726 (1/4" thick)

Strikes: 725-SP Series

SFIC cores: 206/207 Series (page 60)

