

RCI Electronic Access Controls Product Catalog

Switches






906 Handicap Pushbutton

2-3/4"W x 4-1/2"H (70mm x 114mm)



- Blue, 1-3/4" (44mm) diameter button
- Available with handicap symbol screen printed or blank
- Quickly mounts to single gang surface or recessed electrical box
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST), maintained (2-SPST) or time-delay (DPDT) switches available
- · Brushed Stainless Steel (32D) faceplate
- · See accessories at end of this section

How To Order






908 Exit Pushbutton

2-3/4"W x 4-1/2"H (70mm x 114mm)



- Red, black or green, 1-9/16" (40mm) diameter button
- Available with engraved "EXIT" (English, French or Spanish) or blank
- · Quickly mounts to single gang surface or recessed electrical box
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST), maintained (2-SPST) or time-delay (DPDT) switches available
- · Brushed Stainless Steel (32D) faceplate
- · See accessories at end of this section








916 Tamper-Resistant Handicap Pushbutton

Standard: 3"W x 4-3/4"H (76mm x 121mm) Narrow: 1-5/8"W x 4-3/4"H (45mm x 121mm)



- Blue, 1-3/4" (44mm) diameter button
- Available with handicap symbol screen printed or blank
- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- Extruded aluminum 1/4" (6.4mm) plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST), maintained (2-SPST) or time-delay (DPDT) switches available
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized, Dark Bronze (40)
- · See accessories at end of this section

How To Order



¹Standard






918 Tamper-Resistant Exit Pushbutton

Standard: 3"W x 4-3/4"H (76mm x 121mm) Narrow: 1-5/8"W x 4-3/4"H (45mm x 121mm)



- Red or green, 1-9/16" (40mm) diameter button
- Available with engraved "EXIT" (English, French or Spanish) or blank
- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- Extruded aluminum 1/4" (6.4mm) plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST), maintained (2-SPST) or time-delay (DPDT) switches available
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized Dark Bronze (40)
- · See accessories at end of this section






990 Oversized Tamper-Resistant Handicap Pushbutton

3"W x 4-3/4"H (76mm x 121mm)



- · Blue, 2-3/8" (60mm) diameter button
- · Available with handicap label or blank
- Quickly mounts to single gang surface or recessed electrical box or narrow-stile door frames (Narrow)
- Extruded aluminum 1/4" plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST), maintained (2-SPST) or time-delay (DPDT) switches available
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized, Dark Bronze (40) finish
- · See accessories at end of this section

How To Order






990 Oversized Tamper-Resistant Exit Pushbutton

3"W x 4-3/4"H (76mm x 121mm)



- Red or green, 2-3/8" (60mm) diameter button
- Available with "EXIT" and "EMERGENCY" label (English, French or Spanish) or blank
- · Quickly mounts to single gang surface or recessed electrical box
- Extruded aluminum 1/4" plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST), maintained (2-SPST) or time-delay (DPDT) switches available
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized. Dark Bronze (40) finish
- · See accessories at end of this section









Standard: 2-3/4"W x 4-1/2"H (70mm x 114mm) Narrow: 1-3/4"W x 4-1/2"H (41mm x 114mm)



- Blue, 1-5/8" (41mm) diameter button with engraved handicap symbol
- Tamper-resistant, cannot be burned or pried off
- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- UL 508 recognized microswitch
- 1-45 seconds adjustable time delay
- Made in the USA
- · Brushed Stainless Steel (32D) faceplate
- Listed to CSA C22.2 NO. 14-10
- · See accessories at end of this section

How To Order







991 Pneumatic Time Delay Exit Pushbutton

Standard: 2-3/4"W x 4-1/2"H (70mm x 114mm) Narrow: 1-3/4"W x 4-1/2"H (41mm x 114mm)



- Red, 1-5/8" (41mm) diameter button with engraved "PUSH TO EXIT"
- Tamper-resistant, cannot be burned or pried off
- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- UL 508 recognized microswitch
- 0-45 seconds adjustable time delay
- Made in the USA
- · Brushed Stainless Steel (32D) faceplate
- · Listed to CSA C22.2 NO. 14-10
- See accessories at end of this section





919 Rotary Release Pushbutton

3"W x 4-1/2"H (76mm x 114mm)



- Red, 1-3/4" (44mm) diameter button
- Quickly mounts to single gang surface or recessed electrical box
- Push the button once to engage; twist cap in direction of arrows to release
- Designed to prevent users from inadvertently re-engaging the lock
- · Latching momentary action
- · Button must be manually turned to reset
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Maintained (2-SPST) switch operation
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized, Dark Bronze (40) finish
- · See accessories at end of this section

How To Order





920 Emergency Release Keyswitch/Pushbutton

2-3/4"W x 4-1/2"H (70mm x 114mm)



- Red, 1-9/16" (40mm) diameter button
- Quickly mounts to single gang surface or recessed electrical box
- Push the button once to engage; key required to reset
- Designed to prevent users from inadvertently re-engaging the lock
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Maintained (2-SPST) switch operation
- Brushed Stainless Steel (32D) faceplate
- · See accessories at end of this section










917 Easy Touch Pushbutton

2-3/4"W x 4-1/2"H (70mm x 114mm)



- Quickly mounts to single gang box, no mounting box required
- Handicap symbol and English, French and Spanish "Push to Exit" labels included
- Momentary switch operation (SPST)
- · Virtually infinite lifetime
- · Totally weather-proof
- Solid state (no moving parts)
- Pressure sensitive
- Architecturally elegant design
- · Hardware kit includes Allen head screws and wrench
- · Brushed Anodized Aluminum (28) faceplate
- $\boldsymbol{\cdot}$ See accessories at end of this section

How To Order



972 All-In-One Illuminated Pushbutton


2-3/4"W x 4-1/2"H (70mm x 114mm)



¹LED not included

All-in-one button, reduces inventory SKU's

- Large 2" (51mm) square illuminated LED pushbutton
- Includes 3 messages, "Exit", "Push to Exit", and "Occupied When Lit" in English/Spanish or English/French; and a Handicap symbol
- Includes three colored lenses (green, red & clear)
- · Quickly mounts to single gang box
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary switch operation (SPDT)
- Integrated 30 sec. fixed or adjustable delay timer option available
- · SPDT switch is a UL recognized component
- ADA Compliant
- Brushed Stainless Steel (32D) faceplate
- See accessories at end of this section











970 Illuminated Exit Pushbutton

Standard: 3"W x 4-3/4"H (76mm x 121mm) Narrow: 1-5/8"W x 4-3/4"H (41mm x 121mm)



- Illuminated pushbutton
- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- Extruded aluminum 1/4" (6mm) plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (2-SPST or 4-SPST), maintained (2-SPST or 4-SPST) or time-delay (DPDT) switches available
- 12 and 24VAC/VDC options available
- · Optional audible alert add-on
- · Blue (standard), yellow, green, red lens options
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized, Dark Bronze (40) finish
- See accessories at end of this section


975 Illuminated Exit Pushbutton


Standard: 3"W x 4-3/4"H (76mm x 121mm) Narrow: 1-5/8"W x 4-3/4"H (41mm x 121mm)



- 1" (25mm) square illuminated LED pushbutton, green lens
- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- Extruded aluminum 1/4" (6mm) plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- 12 and 24VAC/VDC options available
- Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized, Dark Bronze (40) finish
- Momentary (2-SPST) or time-delay (DPDT) switches available
- See accessories at end of this section

How To Order









980 Economy Pushbutton

2-3/4"W x 4-1/2"H (70mm x 115mm)



- · Quickly mounts to single gang box
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Momentary (SPST), maintained (SPST) or time-delay (DPDT) switches available
- ${\boldsymbol{\cdot}}$ White cap with black trim
- Brushed Stainless Steel (32D) faceplate
- $\boldsymbol{\cdot}$ See accessories at end of this section

How To Order

			Sv	vitch Mod	6
		MO	-Mo	omentary	
		MA	-Mo	aintained	
		TD	-Tir	ne-Delay	
980	-		X	32D	


903 Audible Alert

3"W x 4-3/4"H (76mm x 121mm)



- · For remote or local monitoring
- Quickly mounts to single gang box (Standard) or narrow stile door frames (Narrow)
- Extruded aluminum 1/4" (6mm) plate with beveled edges for tamper-resistance and durability
- Hardware kit includes stainless steel tamper-proof screws and spanner bit
- Push-on wire connectors included
- Field-selectable continuous or intermittent tone (80-96dB)
- · 30mA, 10-26VDC
- Available in Brushed Anodized Aluminum (28) or Brushed Anodized Dark, Bronze (40) finish
- See accessories at end of this section

How To Order



¹Standard



960 Tamper-Resistant Keyswitch

Standard: 3"W x 4-3/4"H (76mm x 121mm) Narrow: 1-5/8"W x 4-3/4"H (41mm x 121mm) Key cylinder sold separately.



- Quickly mounts to single gang box (Standard) or narrow-stile door frames (Narrow)
- Extruded aluminum 1/4" plate with beveled edges for tamperresistance and durability
- · One-piece bracket with two-position switch holder
- Compatible with standard mortise cylinders with straight or clover cams in 1-1/8" or 1-1/4" cylinder lengths (1-1/4" key cylinders available)
- · Momentary (SPDT/DPDT), maintained (SPDT/DPDT) or time-delay (2-SPDT) switches available
- · Hardware kit includes stainless steel tamper-proof screws and spanner bit
- · Faceplate available in Brushed Anodized Aluminum (28) or Brushed Anodized, Dark Bronze (40) finish
- · See accessories at end of this section

How To Order

Faceplate Finish Brushed Anodized -**Options** Aluminum³ Brushed Anodized Dark DPDT1-40 – Bronze 960 Narrow-Stile — Momentary — MO MO -Momentary **Options** Maintained - MA MA - Maintained Time-Delay — TD Options² Switch Mode

¹Only available with MO and MA switch mode

3Standard

Accessories

Model	Description
96-CYLKA	Mortise cylinder, straight cam, keyed alike
96-CYLKD	Mortise cylinder, straight cam, keyed differently

See page 62 for additional accessories




960RO Tamper-Resistant Keyswitch with **Reset/Override**

Standard: 3"W x 4-3/4"H (76mm x 121mm) Narrow: 1-5/8"W x 4-3/4"H (41mm x 121mm) Key cylinder sold separately.



- · Quickly mounts to single gang box
- Extruded aluminum 1/4" plate with beveled edges for tamper-resistance and durability
- · One-piece bracket with two-position switch holder
- · Compatible with standard mortise cylinders with straight or clover cams in 1-1/8" or 1-1/4" cylinder lengths (1-1/4" key cylinders available)
- Momentary (SPDT/DPDT), maintained (SPDT/DPDT) or time-delay (2-SPDT) switches available
- · Hardware kit includes stainless steel tamper-proof screws and spanner bit
- · Screen-printed reset/override with directional arrows indicate the function of corresponding switch model
- · Brushed Anodized Aluminum (28)
- See accessories at end of this section

How To Order



Only available with MO and MA switch mode

Accessories

Model	Description
96-CYLKA	Mortise cylinder, straight cam, keyed alike
96-CYLKD	Mortise cylinder, straight cam, keyed differently

See page 62 for additional accessories



904P Emergency Pull Station

3-9/16"W x 4-1/2"H (91mm x 114mm)



- Heavy-duty polycarbonate design with easy to lift clear Lexan cover
- All-in-one design includes English, French and Spanish labels to apply during installation
- Mounts over standard surface or recessed electrical utility box
- · Maintained (DPDT) switch operation
- 3A at 125VAC
- · Available in Blue finish

How To Order



¹Standard



913 Microwave Motion Switch

4-5/8"W x 4-5/8"H (117mm x 117mm) & 2-3/4"W x 4-5/8"H (70mm x 117mm)



- Doppler radar technology allows for use in sterile environments (i.e. healthcare, food processing plants)
- It can be placed unobtrusively in a room or hallway when mounted behind a non-reflective surface for a clean non-visible solution
- Includes single and double gang plate
- Variable adjustment of pattern depth from 4" to 24" (102mm - 610mm)
- · No wearing parts mean increased product life
- Water-resistant foam gasket provides increased durability when product is exposed to water or cleaning product
- 12 to 24 VDC/VAC
- · Contact rated at 1A
- Available in Black, Cream or White finish
- · Certifications: EMC, FCC, IC

How To Order






909 Rocker Switch

Surface-mount: 2-7/16"W X 2-7/16"H x 7/8"D (61mm x 61mm x 22mm) Flush-mount: 3-7/16"W x 3-7/16"H x 5/8"D (87mm x 87mm x 16mm)



- Ideal for desk or wall mount applications
- Surface-mounts under desk or counter for concealment
- Smooth action rocker with key symbol
- · Momentary (SPDT) and maintained (SPDT) switches available
- 10A at 250VAC
- Beige finish

How To Order



Mode¹Available in surface-mount design only

Switch



914 Sounder

4-3/4"W x 5-9/16"H (119mm x 142mm)



- Ideal for delayed egress applications
- Field-selectable volume output up to 102db
- · Models available for interior or exterior applications
- · Not suitable for mounting on ceilings
- · Easy installation surface wall mounted
- 63mA, 12-24VAC
- · Available in White or Red

How To Order



¹Only available in red finish



915 Passive Infrared

Hands-free egress switch. 6-1/4"W x 1-13/32"H x 1-1/2"D (159mm x 36mm x 38mm)



- Field-Selectable 12/24VDC
- 38mA max at 24VDC, 35mA at 12VDC
- · Hands free release for electromagnetic locks
- · Ideal for "request to exit" with electromagnetic locks
- · Adjustable setting for precise detection area desired
- · Adjustable-relay latch time delay (2-60 sec)
- Two Form C relays (rated 2A at 30VDC)
- SPDT switch configuration
- · Available in Gray or Black

How To Order

Finish Black - B Gray - G



915AFI Active Focused Infrared

6-7/8"W x 1-7/8"H x 2"D (175mm x 48mm x 51mm)



- Mounts on or above the door frame with infrared beam directed near door hardware for pinpoint accuracy and operation, preventing circumvented entry by sliding objects under the door.
- Multiple relocking modes for any timed or door position conditions
- Relay output consists of two Form "C" contacts for NO/NC wiring
- Integrated local sounder with adjustable volume and activation LEDs
- 3 additional auxiliary inputs: request to exit, card reader and a door position switch
- 12 to 24 VDC/VAC
- · Black finish
- Certifications: UL 294/ULC S319

How To Order

915AFI x B




946 Square Push Plate

4-1/2" Sq. (114mm) 4-3/4" Sq. (121mm) 6" Sq. (152mm)



- Available in three sizes
- Momentary (SPDT) switch operation, DPDT accessory kit available
- · Tamper-resistant
- Brushed Stainless Steel (32D) finish
- $\boldsymbol{\cdot}\:$ See accessories at end of this section

How To Order



Accessories

Model	Description
9466SUR	Surface-mount box for 6" push plate
946475SUR	Surface-mount box for 4.75" push plate
94645SUR	Surface-mount box for 4.5" push plate
9466FLU	Flush mount box for 6" push plate
946475FLU	Flush mount box for 4.75" push plate
946475WR	Weather ring for 4.75" push plate
946DGPLATE	Back plate for double gang electrical box
9464PLAST	Double gang mount box
P94/5DMO	DPDT accessory kit

See page 56 for additional accessories




950 Round Push Plate

4-1/2" Dia. (114mm) 6" Dia. (152mm)



- 4-1/2" buttons designed for 2" \times 4" (51mm \times 102mm) switch boxes and 6" buttons designed for 4" \times 4" \times 1-1/2" (102mm \times 102mm \times 38mm) junction boxes
- Available in two sizes
- Momentary (SPDT) switch operation, DPDT accessory kit available
- Tamper-resistant
- Brushed Stainless Steel (32D) finish
- See accessories at end of this section

How To Order



Accessories

Model	Description
9466SUR Surface-mount box for 6" push plate	
946475SUR	Surface-mount box for 4.75" push plate
94645SUR	Surface-mount box for 4.5" push plate
9466FLU	Flush mount box for 6" push plate
946475FLU	Flush mount box for 4.75" push plate
946475WR	Weather ring for 4.75" push plate
946DGPLATE	Back plate for double gang electrical box
9464PLAST	Double gang mount box
P94/5DMO	DPDT accessory kit

See page 56 for additional accessories



946T Square Short-Range Touchless Actuator

4-3/4" Sq. (121mm)



- Low-profile touchless actuator plate utilizing unique capacitive technology for the activation of automatic doors
- Illuminated LED mounting ring for unparalleled durability, visibility and convenience
- Hands-free helps reduce the spread of germs and bacteria
- Short-range adjustable detection zone reduces unwanted activations
- · Adjustable visual and audible alerts
- Field-selectable 12-24 VAC/VDC, 37mA typical
- NEMA 4-rated enclosure
- Made of stainless steel (faceplate) and clear polycarbonate (mounting ring, backplate and enclosure)
- · Momentary (SPDT) switch operation
- Certifications & testing:
 - ANSI American National Standards Institute
- AAADM American Association of Automatic Door Manufacturers
- AIA American Institute of Architects
- FCC Federal Communications Commission
- IDA International Door Association
- DASMA Door & Access Systems Manufacturers Association
- NEMA 4 National Electrical Manufacturers Association
- · See accessories at end of this section

How To Order





950T Round Short-Range Touchless Actuator

6" Dia. (173mm x 152mm)



- Low-profile touchless actuator plate utilizing unique capacitive technology for the activation of automatic doors
- Illuminated LED mounting ring for unparalleled durability, visibility and convenience
- Hands-free helps reduce the spread of germs and bacteria
- Short-range adjustable detection zone reduces unwanted activations
- · Adjustable visual and audible alerts
- · Field-selectable 12-24 VAC/VDC, 37mA typical
- NEMA 4-rated enclosure
- Made of stainless steel (faceplate) and clear polycarbonate (mounting ring, backplate and enclosure)
- Momentary (SPDT) switch operation
- · Certifications & testing:
- ANSI American National Standards Institute
- AAADM American Association of Automatic Door Manufacturers
- · AIA American Institute of Architects
- FCC Federal Communications Commission
- IDA International Door Association
- DASMA Door & Access Systems Manufacturers Association
- NEMA 4 National Electrical Manufacturers Association
- · See accessories at end of this section

Туре									
		Н	-Hai	ndica	p & W	ave Symb	ol		
HW –Handicap & Wave Symbol & "Wave To O W –"Wave To Open" & Wave Symbol						ve To Open"			
	950T		6	-	MO	×	32D		



ILO6 Controller Barrier free washroom controller

Recent building code changes require several enhancements to meet Barrier Free Washroom requirements, with emphasis on emergency assistance. RCI's new ILO6 controller meets and exceeds these requirements.



Energy Input 12-24VDC



Energy Output 61A @ 24VDC relay outputs SPDT



Indicators 14 red/green I/O indicators; 3 digit 8-segment LED display



Input/Output 6 individual inputs and outputs

7 pre-programmed functions (with room for additional functions):

- Function #1: Barrier-free washroom control with emergency call.
- Function #2: Barrier-free washroom control with controlled access and emergency call.
- Function #3: Communicating washroom with auto-operator control and emergency call.
- Function #4: Communicating washroom with emergency call.
- Function #5: 2-Door security interlock with emergency release (mantrap closed and locked continuous).
- Function #6: 2-Door safety interlock with emergency release (air lock closed and unlocked).
- Function #7: Multi-zone control.

6-zone control interface

ILO6 sold as a single controller or as part of a complete kit (ILO6KT) that includes the following items:

- · ILO6 door controller
- · Interior & exterior handicap push plates
- · Push to lock button
- · Interior & exterior annunciator (audible/visual indicators)
- · Surface applied door contact
- Emergency call sign (will vary by province & state)





910TC Touchless Switch 910TC-HC Touchless Switch

2-15/16"W x 4-11/16"H



- Unique low-profile touchless actuator plate utilizing capacitive technology for the activation of automatic doors.
- · Aesthetically pleasing design.
- Hands-free helps reduce the spread of germs and bacteria.
- Adjustable detection zone to reduce unwanted activations.
- When the device is activated, the indicator light (waving hand) will change color.
- $\boldsymbol{\cdot}$ Two plate designs to select from
- Secondary Normally Open (NO) mechanical switch in the event of a power loss.
- · Selectable unlock times (1-63 seconds).
- $\bullet \ \ \text{Mounts on single-gang electrical box}.$
- Available remote control to trigger switch remotely.
- May be purchased as a kit (910TC-WRM-WRB). Includes 910TC Switch, 910TC-WRM Remote Receiver Module and 910TC-WRB Remote Transmitter.
- Certifications & testing:
 - FCC
 - · ISED
- Meets ADA compliance to ANSI/BHMA A156.19.
 (Always check local building codes for compliance in your area)
- See accessories at end of this section

		Тур	oe e		
	WRM-WRB	-Remote Module & Remote Transmitter			
	WRM	-Remote Module			
910TC	WRB	-Remote Transmitter			
910TC-HC		- Gesture control touchless switch			
			Gesture control touchless switch (with wheelchair plate icon)		



940 Rectangular Push Plate

2-3/4"W x 4-1/2"H (70mm x 114mm)



- · Large rectangular faceplate
- Beveled edges provide a tamper and vandal resistant solution
- Universal touch area; push at any location
- Momentary (SPDT) switch operation, DPDT accessory kit available
- Text and symbols are baked onto the surface for maximum durability
- Brushed Stainless Steel (32D) finish
- See accessories at end of this section

How To Order

		Тур	e						
	Н	-Hai	Handicap Symbol						
	HP	-Hai	-Handicap Symbol + Push to Open						
	PTE	-Pus	-Push to Exit						
	В	-Bla	lank						
940		-		×	32D				
			MO	-Mon	nentar	y (SPDT) ¹			
				Swit	ch Mo	de			

¹Standard

Accessories

Model	Description
940SUR	Surface-mount box
P94/5DMO	DPDT accessory kit

See page 62 for additional accessories




941 Mullion Push Plate

1-1/2"W x 4-3/4"H (38mm x 121mm)



- Narrow design makes an easy application on guide rails and swing doors
- Beveled edges provide a tamper and vandal resistant solution
- · Universal touch area; push at any location
- Momentary (SPDT) switch operation, DPDT accessory kit available
- Text and symbols are baked onto the surface for maximum durability
- · Available in Brushed Stainless Steel (32D) or Blue (BLU) finish
- · See accessories at end of this section

How To Order



Options ¹Available only in 32D finish

Accessories

Model	Description
941SUR	Surface-mount box
941FLU	Flush mount box
P94/5DMO	DPDT accessory kit

See page 62 for additional accessories

²Available only with HP and H type in 32D finish



9LP36 Low Profile Push Plate

6"W x 36"H (152mm x 915mm)



- An all-active plate activates with any "push" location
- Can be mounted to any flat surface using concealed fasteners for aesthetics and to minimize vandalism
- Easily adapts to either a wireless or hardwired installation
- Optional built-in wireless transmitter comes pre-installed in the top end cap
- UL Listed push plate for pedestrian door activation under UL325 for US and Canada
- Exceeds the California Building Code, Section 1117B.6
- Exceeds Ontario Building Code, Sections A-3.8.3.3 (17) and A-3.8.1.5
- · Brushed Stainless Steel (32D) finish

How To Order

			Type			
		HW	-For	r Hardwire Installation		
		433	-For	Wireless Installation (433MHz Transmitter)		
9LP36	-		X	32D		



9RCT433/9DRCR433 Transmitters & Receivers

2-3/4"W x 2-1/8"H x 1"D (70mm x 55mm x 14mm)



- · An all-active plate activates with any "push" location
- Can be mounted to any flat surface using concealed fasteners for aesthetics and to minimize vandalism
- Easily adapts to either a wireless or hardwired installation
- Optional built-in wireless transmitter comes preinstalled in the top end cap
- UL Listed push plate for pedestrian door activation under UL325 for US and Canada
- Exceeds the California Building Code, Section 1117B.6
- Exceeds Ontario Building Code, Sections A-3.8.3.3 (17) and A-3.8.1.5
- · Brushed Stainless Steel (32D) finish

How To Order Transmitter

9RCT433		
	1	-One Button
	2	-Two Buttons
	3	-Three Buttons
	4	-Four Buttons
	3V1	-One Button Wired With 3V Battery
	9V1	-One Button Wired With 9V Battery
	7 V I	Lead
		Type

How To Order Receiver

9DRCR433		
		-Receiver
	EHT	-Receiver With Extended Hold Time
		Type



2 Pin

9500/9501 Mortise Pin Transfers

1/2"W x 2-3/4"H (13mm x 71mm)



· Recessed in the hinge side of the door/frame

and concealed when the door is closed for



9501

3 Pin

1.5A at 24VAC
 Made of picks

tamper-resistance

- · Made of nickel-plated brass and plastic
- · White finish

How To Order





9503 Mortise

9503 Ball Transfer

1/2"W x 2-3/4"H (13mm x 71mm)



- Recessed or surface-mounted on either hinge side, lock side or frame header. Recessed models are concealed when the door is closed for tamper-resistance
- 500mA at 24VAC
- Contact pins are hard gold-plated (corrosion-free)
- · White finish

How To Order





9507/9509 Flex Loops



9507

- · Surface-mounted on hinge side
- Accepts 4-conductor @ 22 gauge or 2-conductor @ 18 gauge (not included)
- · Made of stainless steel coated brass
- · Available in Silver, Brown and White finish

9509

- Surface-mounted on hinge side
- · Heavy-duty flex loop with increased conductor capacity
- Accepts 16-conductor @ 22 gauge or 8-conductor @ 18 gauge (not included)
- Made of stainless steel
- · Silver finish

How To Order



19509 available in Silver only



9520/9521/9522 9523/9524 Electrified Hinges

9520 4" x 4" (102mm x 102mm)

9521 4-1/2" x 4" (114mm x 102mm)

9522 4-1/2" x 4-1/2" (114mm x 114mm)


9523 5" x 4-1/2" (127mm x 114mm)

9524 5" x 5" (127 mm x 127mm)



- Five knuckle
- Standard weight
- Fully mortised in the hinge stile and concealed when the door is closed for tamper-resistance
- Made of steel
- 6-conductors (4 at @ 22 gauge, 2 @ 18 gauge) included
- Available in Brushed Chrome (26D) or Brushed Stainless Steel (32D) finish

How To Order



Finish

RCI Power Transfers and Door Contacts




9512/9513 **Bridge Cables**

9512 Visible face: 1"W x 12-3/4"H (25mm x 324mm) Recessed: 7/8"W x 10-3/16"H (23mm x 259mm)

9513 Visible face: 1"W x 21-7/16"H (25mm x 545mm) Recessed: 7/8"W x 18-7/8"H (23mm x 479mm)





- · 4-conductor @ 22 gauge or 2-conductor @ 18 gauge
- · Made of steel
- · Bright Chrome (26) finish

How To Order

		Туре			
	2	-12-3	3/4" H (32	4mm)	
	3	-21-7	7/16" H (5	45mm)	
951		Х	26		



9540 Recessed Magnetic **Contact/Door Position** Switch

3/4"W x 3/4"H x 7/8"D (19mm x 19mm x 22mm)



- 200mA Max, 30VAC/VDC
- 3/4" (19mm) dia. recessed magnetic contact
- 12" #22 AWG wire leads
- · Rare earth magnet
- · Self-locking in steel and wood
- · End-of-line resistors, diodes and supervisory
- · Loop type: open/closed
- SPDT configuration
- · Available in White or Black finish



9530 Balanced Magnetic Contact/Door **Position Switch**

3-1/2"W x 1-1/4"H x 5/8"D (89mm x 32mm x 16mm)



- 50mA Max, 100VDC
- · Surface-mount switch and magnet
- · Utilizes two Form C high reliability Rhodium plated reed switches, one of the two reed switches being of different sensitivity, encapsulated in epoxy inside a solid aluminum case
- · SPDT switch configuration with magnetic tamper
- · When the rare earth magnet is in place and properly adjusted (balanced), the magnetic tamper switch 2 will be in a state opposite to the switch 1
- · This normal configuration will change should one of the following occur; (1) switches 1 and 3 will change state by either the deliberate shunting of the magnetic field or if the door window is opened, and (2) the addition of a magnetic field such as an external magnet will cause the magnetic tamper switch 2 to change state
- · End-of-line resistors may be used to allow a predetermined trickle of current to flow and permit operation from a supervised line at all times
- 18" Armored Cable, #22 AWG Wire Leads

How To Order

9530



RCI Switches Accessories



TD30/TD30A Timer Delay

Model	Description
TD30	30 sec. fixed timer (12/24VDC)
TD30A	0 to 30 sec. adjustable timer (12/24VDC)



910TC-WRM Remote Receiver Module

Model	Description		
910TC-WRM	433MHz remote receiver module		



910TC-WRB Remote Transmitter

Model	Description		
910TC-WRB	433MHz remote transmitter		

P94/5DMO DPDT Switch Kit

Model	Description				
P94/5DMO	DPDT momentary contact switch kit				

Compatibility

Model	9SURBOX	TD30	TD30A	P94/5DMO
903 Audible Alert	•	-	_	_
904P Emergency Pull Station	•	-	-	-
906 Handicap Pushbutton	•	•	•	-
908 Exit Pushbutton	•	•	•	-
909 Rocker Switch	-	•	•	-
916 Tamper-resistant Handicap Pushbutton	•	•	•	-
917 Easy Touch Pushbutton	•	•	•	-
918 Tamper-resistant Exit Pushbutton	•	•	•	-
919 Rotary Release Pushbutton	•	-	-	-
920 Emergency Release Keyswitch/Pushbutton	•	-	-	-
940 Rectangular Push Plate	•	•	•	•
941 Mullion Push Plate	-	•	•	•
946 Square Push Plate	•	•	•	•
946T Square Short-Range Touchless Actuator	•	•	•	-
950 Round Push Plate	•	•	•	•
950T Round Short-Range Touchless Actuator	•	•	•	-
960 Tamper-resistant Keyswitch	•	•	•	-
970 Illuminated Exit Pushbutton	•	•	•	-
972 All-In-One Illuminated Pushbutton	-	•	•	-
975 Illuminated Exit Pushbutton	•	•	•	-
980 Economy Pushbutton	•	•	•	-
990 Oversized Tamper-resistant Handicap/Exit Pushbutton	•	•	•	-
991 Pneumatic Time Delay Handicap/Exit Pushbutton	•	-	-	-

dormakaba Canada Inc. 65 Struck Court Cambridge, ON Canada N1R 8L2 Tel: 800-265-6630 sales_RCI@dormakaba.com

www.dormakaba.us