



CS Series

ANSI Grade 2 Heavy Duty Clutched Cylindrical Lockset



RELIABLE

Heavy & Standard Duty

DURABLE

Withstands extreme abuse

DEPENDABLE

Patented reinforced springs eliminate lever sag.

CS Series

NEW Grade 2 Heavy Duty **CLUTCHED** Cylindrical lockset



FEATURES

- Quality machined stainless steel hubs mounted with heavy duty return springs eliminate the possibility of lever sag.
- A stronger rose-liner material provides greater protection from extreme abuse.
- Heat treated steel spindles provide long lock life.
- Threaded outside rose assembly adjustable for door thickness without removing keyed lever.
- Outside clutching lever to protect lock against abuse.

Specifications

Door Thickness	1-3/8" to 2-1/4" wood or metal doors.
Backset	2-3/4" standard, 2-3/8" optional.
Latchbolt	1/2" throw, UL listed, faceplate self-adjusted.
Handing	Non-handed. ADA compliant.
Strike	T-strike standard, full-lip strike optional.
Trim	Solid zinc diecast levers, wrought brass roses, concealed screws.
Door Preparation	ANSI A115.2, through bolt installation.
Cylinder	Standard solid brass 6-pin "C" keyway, 2-keys.
Master Keying	Can be master keyed or grandmaster keyed. Construction key systems available.
Finishes	605, 606, 613, 619, 625, 626.
Certifications	UL listed for "A" label, 3 hours fire rated, single swinging door (4'x8').
Standard Tested	ANSI A156.2, Series 4000 Grade 2.




Sentinel Standard trim in 626



Quest Standard trim in 605

How To Order

Series	Function	Lever	Finishes
CS - Standard Cylinder	See Function page.	Sentinel (S) Quest (Q)	605 (Bright Brass) 606 (Satin Brass) 613 (Oil Rubbed Bronze) 619 (Satin Nickle) 625 (Bright Chrome) 626 (Satin Chrome)



Latch



T-Strike

Ordering Example

1. CS Series Lock
2. Entry/Office Function
3. Lever
3. Satin Chrome Finish

CS **81** **Q** **626**

