General Hardware



SECURITY SURFACE BOLTS

GH-UL831/UL453



GH-UL831

- Concealed mounting
- Tamper proof
- **UL** listed
- 8" Long
- 1" throw, 1%" projection
- Finishes: US26D



GH-UL453

- Surface mounting
- Tamper proof
- **UL Listed**
- 8" Long
- $1^{1}/_{16}$ " throw, 1%" projection
- Finishes: US26D, ZP

FLUSH BOLTS



- GH-ULSB197: UL fire rated
- GH-197: Extruded Aluminum
- Non handed
- %" throw with %" vertical adjustment
- 12" rod to fit ANSI prep.
- Spring loaded lever
- 1/2" dia. brass bolts
- Finishes: US3, 26, 26D

GH-1057

FOOT BOLT

Specifications

- Foot bolt 6"
- Operated by pressure of foot on cap
- Released by pressure on tip
- Packaged with screws and strike
- Finishes: Zinc plated



SECURITY BOLT

GH-835SE



Specifications

- Steel security bolt
- Heavy duty
- Durable silver sprayed epoxy finish
- 9" with 11/2" projection
- Surface or motise application
- Polybagged with fasteners
- Finishes: AL

BARREL BOLT

GH-832BB



Speficiations

- 5" and 8"
- Locking and padlockable
- Extra heavy duty
- Rust resistant
- Heavy zinc plated bolt, 9/16" dia.
- Finishes: GV



CHAIN BOLT

GH-1055

Specifications

- Chain bolt 6"
- Packaged with screws and strike
- Finishes: Zinc plated



CHAIN GUARD

GH-1631/DX3700

GH-1631

- Adjustable 20"- 30½"
- Heavy duty commercial
- Cast brass mounting plates
- 2 rugged compression springs
- Vinyl cover
- Cast brass mounting and plates
- Finishes: DU, US26D

GH-DX3700

- Single spring
- Pack with fasteners
- Finishes: Zinc Plated



GH-1631



GH-3700

HASPS GH-CD575/CD577/600XHH75



GH-CD575

- Single flexible
- Safety hasp
- 6½"
- Zinc plated



GH-CD577

- Double Flexible
- Safety hasp
- 73/4"
- Zinc plated



GH-600XHH75

- Garage and utility door
- Extra heavy hinge hasp
- 7½"
- Zinc plated

DOOR REINFORCER

GH-DR45/DR90





| MODEL NUMBER | SIZE | BACKSET | DOOR THICKNESS | FINISHES |
|--------------------|------|---------|----------------|----------|
| 4" Door Reinforcer | | | | |
| GH-DRDB101 | 4½" | 2 %" | 1 ¾" | US3, 32D |
| GH-DRDB102 | 4½" | 2 ¾" | 1 ¾" | US3, 32D |
| GH-DRDB103 | 4½" | 2 %" | 1 %" | US3, 32D |
| 9" Door Reinforcer | | | | |
| GH-DRLK104 | 9" | 2 %" | 1 ¾" | US3, 32D |
| GH-DRLK105 | 9" | 2 ¾" | 1 ¾" | US3, 32D |
| GH-DRLK106 | 9" | 2 %" | 1 %" | US3, 32D |

LATCH GUARDS

GH-LG109/LG111



GH-LG109

- Fits all hollow metal or wood doors
- Reversible handing
- Protects cylindrical and mortise locks and guards latch bolt
- Mounts to door with heavy duty sex bolts
- Finishes: US26D



GH-LG111

- Fits narrow line aluminum doors
- Reverisble handing
- Tamper-proof
- Mounts to door with heavy duty sex bolts
- Finishes: AL, DU

DOOR VIEWERS

Door viewers are made with safety and durability in mind. Solid cast brass with highly polished optic lenses for extra wide viewing angles.

Specifications

- 13/4" thick wood or metal doors
- Solid cast brass
- UL: Fire rated
- Finishes: US3, 26D



GH-SB190 9/16" bore 190' viewing





GH-UL3300 ½" bore 190' viewing

DOOR CHIME

GH-DCV01

Specifications

- Doors 11/8" 2" thick
- Available in deluxe: GH-DXDCV01
- Two-tone chime
- 180' viewing angle
- Finishes: US3, 26D



DOOR STOPS

FLOOR MOUNTED DOOR STOPS

- Wrought steel and cast brass
- Suitable for all floor conditions
- Bumpers constructed from durable rubber
- Ideal for commercial applications
- Fasteners: screw packs included
- Finishes: US3, 26D

WALL MOUNTED DOOR STOPS

- Wrought steel and cast brass
- Suitable for all wall conditions
- Bumpers constructed from durable rubber
- Fasteners: screw packs included
- GH-DS406: Available in US26D only
- Finishes: US3, 26D







GH-DS438 High Dome Door Stop



GH-DS401 Concave Wall Stop



GH-DS406 Convex Wall Stop

GH-135: 4" Cast alloy door holder

- GH-1135: 5" Cast alloy door holder
- GH-235: 4" Solid brass door holder
- GH-1235: 5" Solid brass door holder
- GH-380: 5" Door holder
- GH-6015: 8" Step on door holder
- Durable rubber tips
- Polybagged with sheet metal screws
- Finishes: US3, 26D
- 6015 Finishes: AL/DU







Drop Down & Step On

MAIL SLOTS

HEAVY BRASS



Exterior Spring Mounting

- Interlocking flap and frame
- Packaged with screws
- GH-HD390: Letter slot 3" x 10"
- GH-HD490: Magazine slot 31/2" x 13"
- Finishes: US3, 5, 26D

Interior Gravity Mounting

- Gravity flap with 1/4" air vent
- Packaged with screws
- GH-HD395: Letter slot 3" x 10"
- GH-HD495: Magazine slot 31/2" x 13"
- Finishes: US3, 5, 26D

Interior Trim Plate

- GH-HD398: Letter slot 3" x 10"
- GH-HD498: Magazine slot 31/2" x 13"
- Finishes: US3, 5, 26D

PULL PLATES

CLASSIC PULL WITH HANDLE

- Aluminum, solid brass, stainless steel materials
- Classic and round pulls
- 16 guage (.050") thick
- Mounting screws for 1¾" thick door
- Packed with sheet metal screws
- Conforms to ANSI J405 and A117.1
- Finishes: AL, US3, 32D

GH-PP5310 3½" X 15" with classic pull **GH-PP5425** 4" X 16" with round pull **GH-PP5325** 3½" X 15" with round pull



PUSH PLATES

GH-PP53/54

- Aluminum, solid brass, stainless steel materials
- Mounting screws for 1¾" thick door
- Packed with sheet metal screws
- Conforms to ANSI J301 and A117.1
- Finishes: AL, US3, 32D

GH-PP53 3½" X 15" **GH-PP54** 4" X 16"





KICK PLATES

COMMERICIAL

- Aluminum, solid brass, stainless steel materials
- Stainless steel available
- 16 guage (.050") thick
- Kick plates not bevelled
- Other sizes and finishes available upon request
- Packed with sheet metal screws
- Conforms to ANSI J102 and ANSI A117.1 for ADA barrier-free accessibility
- Brasstone on aluminum available
- Finishes: AL, BT-AL, US3, 32D



GH-KP834 8" x 34" **GH-KP1034** 10" x 34"

TEE HANDLE

GH-960

- Polished chrome die cast handle
- Heavy duty
- 4" spindle, 5/16" square
- Reversible
- 90 degree turn
- Keying avilalbe: KA, KD
- Packaged with 2 keys
- Finishes: US26



DOOR PULL

GH-P531

- Heavy cast aluminum door pull
- 7 ½" x 1 ½"
- 2 ¼" projection
- Finishes: AL, DU



HARDWARE

BALL CATCHES/ROLLER LATHCES



GH-2945

- Drive in ball catch
- Maximum roller projection: 5/16"
- Latch: 1%"
- Diameter: 1"
- Strike dimensions: 1%" x 2¼"
- Finishes: US3



GH-2950

- Mortise ball catch
- Maximum roller projection: 5/16"
- Latch: 1%"
- Diameter: %"
- Strike dimensions: 1%" x 2¼"
- Finishes: US3



GH-2955

- Roller latch
- Maximum roller projection: 5/16"
- Latch face: 1" x 1%"
- Strike dimensions: 2" x 1%"
- Finishes: US3, 26

MAGNETIC CATCH

GH-CH2935

- Cabinet magnetic catch
- Solid aluminum housing
- Designed for heavy doors
- Holding power up to 35 lbs
- Can be used for double door installation
- Polybagged with screws
- Finishes: AL



CABINET PULLS

GH-CH44840


- 4" cabinet pulls
- Aluminum
- 5/16" diameter
- For cabinet doors ¾" 1¾" thick
- Packed with machine screws
- Finishes: AL, US26D



ADA SIGNAGE

ADA COMPLIANT SIGNAGE

- Raised symbols & letters
- 8" x 8" Pictogram
- Grade 2 Braille
- 3/16" thick polystyrene- ABS with UV stabilizer to avoid fading
- %" raised lettering
- Finishes: Blue, Black





GH-S441 Men



GH-S440 Women



GH-S442 Family Restroom



GH-EXIT Exit



GH-S445 Men Handicap



GH-S443 Women Handicap



GH-S444 Family Handicap



Trans-Atlantic Co.

Architectural Catalog

www.transatlanticco.com

Tel: 800.523.9956 Fx: 800.531.0844