

Category 5 Black and White Bullet Camera Kit

CM7645



This black and white camera kit features the same capabilities as the color camera kit, but in a more affordable package. Based on Cat 5 cabling, installation is cost effective and simple. Included cameras are weatherproof and good for indoor or outdoor applications.

features & benefits

Kit Includes:

- 1 CM1011 CAT5 Camera Module
- 2 F2284 Black and White Bullet Cameras
- 1 F1001 Modulator with power supply
- 1 CM1017 RCA Patch Cable
- 1 PW7725 Power Supply

Requires part number F7642 for audio use.

specifications

General Info

Cable Type: RCA Patch Cable: RG Shielded Coaxial Cable
Color: Modulator: Black
Cameras: White
Camera Module: Gray
Connection Type: Patch Cable: RCA, Gold Plated
Type: Camera/Modulator Kit
Input Plug Type: Camera Module: 4 x RJ45 Input Jacks
Modulator: F Connector

Listing Agencies/Third Party Information

UN SPS C: 45111801

Dimensions

Depth U S: Modulator: 4.75
Height U S: Modulator: 1.625"
Width U S: Modulator: 3.625 in

Cord Information

Connector Type End One: Patch Cable: 1 x RCA Plug
Connector Type End Two: Patch Cable: 1 x RCA Plug
Cord Length U S: Patch Cable: 12.0"

Technical Information

AC Voltage Input: Modulator: 110 V Power Supply included
Amps: 800 mA
Compatible Power Supplies: LCD Module: PW7725 (included)
Frequency: UHF: Channels 14 to 69
Cable: Channels 60 to 94 and 100 to 125
Frequency Response: Modulator: +/-3 dB max from 100 Hz to 10K Hz with 1K Hz as a reference
Jack Connectors: RJ45 and RCA
Material: Faceplate: Plastic ABS
Ohm Value: Patch Cable: 75 Ohm
Modulator: 10K Ohm min input impedance from 1K Hz to 10K Hz
Operating Temperature Celsius: -10°C to 50°C
Operating Temperature Fahrenheit: 14°F to 122°F
Output And Line Out Connection: Camera Module: 4 x RCA Audio Out, 4 x RCA Video Out, 1 RCA Video Sequence Out
Volts D C: Camera Module: 12 VDC
Watts: Camera Module: 9.6 W max