



5.8GHz 4CH DVR

IV-5844-Kit

Features:

- . Moveable antenna for best performance
- . H.264 baseline: 9 selectable video quality levels
- . 5 network clients supported
- . Network audio conferencing capability
- . Playback search by time or event (alarm, motion & video loss)
- . Multi - lingual support
- . Recording quality can be configured into group - better usage of hard disk
- . Multi - level password to ensure high degree of security
- . Removable HD rack(38294)
- . Hi Res Cameras with 6mm lens and IR LEDs
- . Cameras include individual power supplies



SPECIFICATION	IV-5844-Kit
Wireless Camera Power	25 ~ 100 mW
Frequency Range	5645 ~ 5945 MHz
Channel Frequency	CH1: 5945 MHz CH2: 5845 MHz CH3: 5745 MHz CH4: 5645 MHz
Input Signal Level Range	- 85 ~ - 10 dBm
Antenna	Omni - Directional (Antenna Gain 5 dBi)
Video Level Control	FM
RF Level Control	AGC
Noise Figure	3 dB
Video Input Format	NTSC: BNC 4CH In/ 1CH Out / SPOT Out
Display Resolution	NTSC: 720 x 480
Recording Frame Rate(IPS) & Resolution	NTSC: 30 / 720 x 480; 60 / 720 x 240; 120 / 360 x 240
Compression Method	Video: H.264 Baseline Audio: ADPCM
Hard Disk Capacity	80-500G Bytes, ATA - 100 interface HDD x 1
Recording Time	7 ~ 20 days with 500GB HD for continuous recording mode @ 25 fps
Recording Mode	Continuous, Motion detection, Sensor activated, Time schedule
Sensors, Alarm	4 Input, 1 Output (Alarm)
Audio	2 CH in, 2 CH out
Network	1 RJ -45 10/100 Mbps Ethernet Connector
Media Backup	1 SD slot(Optional) / 1 USB 2.0 ports for USB 2.0 flash disks,
	DVD+RW, DVD+R, card readers, HDD
VGA Output	1 CH
PTZ Control	RS-232
IR Remote Controller	Yes
Operating Temperature	0° ~ +50 °C
Power Supply	DC 12V / 5A
Dimension (L x W x H)	12.4" x 10" x 2.05" (315mm x 250mm x 52mm)