

AVS-B2110

1.3 Megapixel 720P Weather-proof IR HD-AVS Camera

- 1/3" 1.3 Megapixel CMOS
- 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens
- Max. IR LEDs length 65ft, Smart IR
- IP66, DC12V

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

AVS-B2110

1.3 Megapixel 720P Weather-proof IR HD-AVS Camera

Model	AVS-B2110
Camera	
Image Sensor	1/3" 1.3Megapixel CMOS
Effective Pixels	1280(H)x960(V)
Electronic Shutter	4/30~1/54,000s
Video Frame Rate	1280x720@50 fps ; 1280x720@60 fps
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2(0Lux IR LED on)
Video Output	1-channel BNC HD-AVS high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	65ft Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Support
Lens	Lens
Focal length	3.6mm fixed lens
General	
Power Supply	DC12V ±10%
Power Consumption	Max 7.7W
Working Environment	-14°F - 122° F (-25°C - 50° C) 90% RH (no condensation)
Transmission Distance	Over 1640 feet via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions(WxDxH)	Φ7.88"x3.5"x3.17" - Φ200.2mmx89.1mmx80.4mm
Weight	450g