

ICIP-S3000AF

3 Megapixel Indoor/Outdoor, Full-Size IP Bullet IR Camera



A weatherproof, day/night, 3 Megapixel, full-bodied bullet camera – the ICIPS3000AF. This full box style design contains a high resolution 3 Megapixel Sony Progressive Scan Exmor CMOS sensor, capable of outputting a crisp and clear image. The optics on this camera are located behind the removable front bezel, which conceals the 8-16mm vari-focal lens. The removable front glass also contains a high intensity LED ring, suitable for 100' of viewing with 0 light. This camera is IP 66 rated and highly weatherproof.

Features

- Built-in 8~16mm/F1.6 CS Auto Iris lens
- Built-in high-performance IR LEDs(60~100 ft)
- 15fps at 3.0M(2048x1536)
- High-performance TI DaVinci series DSP
- Support ICR true Day/Night

ICIP-S3000AF

Specifications

Model	ICIP-S3000AF
General	
Processor	TI DaVinci Series DSP
Operating System	Embedded LINUX
Resource	Simultaneous remote monitoring, local recording and remote control
User Interface	Web, Smart ICRSS, ICRSS Pro/ICVIEW, NVR
Camera	
Image Sensor	1/2.8" 3.0 Megapixel SONY progressive scan Exmor CMOS
Effective Pixels	2096(H)×1561(V)
Electronic Shutter	Auto/Manual, 1/60~1/10000s
Min. Illumination	0.2LUX/F1.6(Color), 0.01LUX/F1.6(B/W), 0LUX(IR on)
Signal Noise Ratio	>50dB
Gain Control	Auto/Manual
White Balance	Auto/Manual
Day/Night	ICR
Lens	CS mount, Auto Iris, 8~16mm /F1.6
Video	
Video Compression	H.264E/MJPEG
Image Resolution	3.0M(2048×1536)/1080P(1920×1080)/720P(1280×720)/D1(704×480) CIF(352×240)/VGA(640×480)
Encoding Speed	Main Stream: 3.0M(1~20fps), 1080P/720P/ D1/CIF/ VGA(1~30fps) Extra Stream: D1/CIF (1~30fps)
Bit Rate	160K~8Mbps
Snapshot	Fastest 1fps JPEG capture
Video Format	NTSC
Analog Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Audio	
Audio Compression	G.711a / G.711u / PCM
Bit Rate	64kbps/128kbps
Input	1 channel RCA
Output	1 channel RCA
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Functions	HTTP,TCP/IP,ARP,IGMP,ICMP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP, DNS,DDNS,PPPOE,UPNP,NTP,Bonjour,SNMP
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade
Auxiliary Interface	
Micro SD Card	Max 32GB, local storage
Alarm	2 Input / 1 Output
Environmental	
Power Supply	DC12V, PoE
Power Consumption	<10W
IR LEDs	60~100 ft

Ingress Protection	IP66
Operating Environment	-40°F ~ 140°F / -40°C ~ 60°C, 10%~90%
Dimensions (WxDxH)	11.35"×4.66"×3.98" (288.3×118.3×101mm)
Weight	5.5lb/2.5kg

ICIP-S3000AF

Optional Accessories



MNT-S3000AF