

# **Essentials**1 MP and 2 MP Varifocal IP Bullet Cameras



#### Features That Make a Difference:

- 1 and 2 megapixels
- 2.8-12mm varifocal lens
- H.264 and MJPEG dual-stream encoding
- Maximum 30 ips
- Multiple network monitoring
- IP66
- PoE
- IR Illumination
- True Day/Night
- Wide Dynamic Range

The Illustra Essentials varifocal bullet camera is available in 1 and 2 megapixel options, can be installed indoors or outdoors and has IR Illumination. The bullet camera can capture video in a variety of lighting situations with features such as True Day/Night and Wide Dynamic Range.

#### **Low Light Clarity**

The Illustra Essentials varifocal bullet camera masters low-light clarity. The sensitivity of the sensor and processor combination is enabled through the latest technology such as True Day/Night. In low light, this camera delivers clear video surveillance.

Poor low-light performance by megapixel cameras hampers some of the most important tasks security professionals need to perform. When cameras lack clarity in low-light, they also tend to increase bandwidth usage and storage costs. Cameras that fail in low-light clarity negatively impact both the necessary functions of security and cost of ownership.

#### Wide Dynamic Range

For applications where the glare of direct sunlight may affect surveillance, WDR is a must-have feature. Only the best performing cameras can manage the contrast created by the backlighting that direct sunlight can produce.

The Illustra Essentials varifocal bullet camera takes advantage of the latest pixel-by-pixel dynamic range offered today. Avoid loss of detail in strongly backlit scenes with the power of WDR. Maintain the details in faces with whole scene clarity. WDR provides rendering of a high-resolution HD image that excels in a wide range of challenging lighting conditions.

## Specifications

	1MP	2MP				
Camera						
Imager	1/3"	1/2.8"				
Resolution	1280 x 720	1920 x 1080				
Shutter Speed	Auto/manual, 1/3(4) – 1/10000s	Auto/Manual, 1/3(4) – 1/10000s				
Minimum Illumination	0. 01 Lux/F1.4 (Color)	0. 01 Lux/F1.4 (Color)				
	0 Lux/F1.4 (IR on)	0 Lux/F1.4 (IR on)				
S/N Ratio	> 55dB	> 50dB				
Analog Video Output	N/A	N/A				
Camera Features						
IR Illuminator	30m	30m				
Day/Night	Mechanical ICR	Mechanical ICR				
Backlight Compensation	Yes	Yes				
Wide Dynamic Range	Yes	Yes				
White Balance	Auto/Manual	Auto/Manual				
Gain Control	Auto/Manual	Auto/Manual				
Digital Noise Reduction	3D	3D				
Privacy Zones	Up to 4 areas	Up to 4 areas				
Lens						
Focal Length	2.8-12mm	2.8-12mm				
Max Aperture	F1.4	F1.4				
Focus Control	Manual	Manual				
Angle of View	H: 92°	H: 98.1°				
Video						
Video Compression	H.264/MJPEG	H.264/MJPEG				
Resolutions	1.3M (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); CIF (352 × 288/352 × 240)	1080P (19020 x 1080); 1.3M (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480); CIF (352 x 288/352 x 240)				
Max Frame Rate	Main stream: 1.3M (30ips)	Main stream: 2M/1MP (30ips)				
	Sub stream: D1/CIF (30ips)	Sub stream: D1/CIF (30ips)				
Audio	N/A	N/A				
Network						
Ethernet	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)				
Wi-Fi	N/A	N/A				
Supported Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour				
ONVIF-Compliant	ONVIF, CGI, PSIA	ONVIF, CGI, PSIA				
Auxiliary Interface						
Onboard Storage	N/A	N/A				
Alarm Input/Output	N/A	N/A				
General						
Power Supply	DC12V, PoE (802.3af)	DC12V, PoE (802.3af)				
Power Consumption	4.5W	4.5W				
Operating Temperature	-30°C to 60°C (-22°F to 140°F)	-30°C to 60°C (-22°F to 140°F)				
IP Rating	IP66	IP66				
Vandal Resistant	N/A	N/A				
Dimensions	72mm × 80mm × 212.8mm (2.83in × 3.15in × 8.38in)	72mm × 80mm × 212.8mm (2.83in × 3.15in × 8.38in)				
Menu Languages	Chinese (simplified), English (default), French, German, Portuguese, Spanish	Chinese (simplified), English (default), French, German, Portuguese, Spanish				
Weight	0.65kg (1.43lbs)	0.65kg (1.43lbs)				



Model	Description
IES01B1BNWIY	Illustra Essentials 1MP Bullet, 2.8-12mm, outdoor, nonvandal, white, TDN w/IR, WDR
IES02B1BNWIY	Illustra Essentials 2MP Bullet, 2.8-12mm, outdoor, nonvandal, white, TDN w/IR, WDR

	ILLUSTRA CAMERA MODEL KEY										
ILLUSTRA	SERIES	MODEL	RESOLUTION	FORM FACTOR	LENS	ENVIRONMENT HOUSING	BUBBLE	COLOR	DAY/NIGHT/IR	WDR	OTHER
1	E = Essentials	L = Lite	01 = 1MP	B = Bullet	N = None	N = None	N = None	B = Black	C = Color Only	N = No	A = Hardware Update
	F = Flex	P = Plus	02 = 2MP	C = Compact Dome	F = Fixed	A = Indoor NonVandal	C = Clear	G = Gray	I = TDN w/IR	T = Multi- Exposure (>60 Frames)	
	P = Pro	S = Standard	03 = 3MP	D = Dome	0 = 1.8 - 3mm	B = Outdoor NonVandal	S = Smoked	S = Silver	S = Soft Day/Night	Y = Yes	
	Q = Edge		05 = 5MP	F = Fisheye	1 = 2.8—12mm	I = Indoor Vandal		W = White	T = TDN		
				M = Mini-Bullet	2 = 3 - 9mm	O = Outdoor Vandal					
				P = PTZ	3 = 9-22mm						
				W = Wireless Cube	4 = 9 - 40 mm						
				X = Box	5 = 20x						
					6 = 30x						

OPTIONAL VARIFOCAL BULLET ACCESSORIES				
Model	PFA122	PFA151	PFA152	
Decription	Junction Box	Corner Mount	Pole Mount	
Dimensions	134mm x 134mm x 55mm (5.28in x 5.28in x 2.16in)	243mm x 170mm x 138mm (9.60in x 6.70in x 5.43in)	117.5mm x 87mm x 21mm (4.60in x 3.40in x 0.83in)	
Weight	0.5 Kg (1.10 lbs)	1.7 Kg (3.75 lbs)	0.2 Kg (0.44 lbs)	
Load Bearing	3.0 Kg (6.61 lbs)	10 Kg (22 lbs)	3.0 Kg (6.61 lbs)	

#### **Related Products**



VideoEdge



exacqVision





### Approvals











www.illustracameras.com