

EasyNet™ HD Weatherproof Bullet

EC-2M-B3N

Specification



KEY FEATURES:

- 1/3" CMOS Sensor
- 2MP (1080p)
- 3.7mm Fixed Lens
- Day/Night Functionality with ICR
- 20 IR LEDs (Up to 50ft)
- Digital Noise Reduction: DNR
- Back Light Compensation: BLC
- Auto White Balance: AWB
- Service Monitor Output (PC-less IP Configuration)
- Built-in PoE/24VAC

CONSTRUCTION:

- 3-Axis Bracket
- Weatherproof Aluminum Housing

AVAILABLE ACCESSORIES:

- CA-ORC: Service Monitor and OSD Controller Cable

TECHNICAL SPECIFICATION:

EasyNet™ HD Weatherproof Bullet	EC-2M-B3N
Resolution	2MP (1080p)
Image Sensor	1/3" CMOS
Day/Night Functionality	Yes
Lens Type (DC Auto Iris)	3.7mm fixed lens
Angle of View	70° (W)
IR LEDs	20
IR LEDs Distance	Up to 50ft.
LEDs Illumination Angle	80°
Video Compression	H.264 / MJPEG
Frame Rate	30fps
Electronic Shutter	1/30 ~ 1/20,000 sec.
Service Monitor Output	1.0 Vp-p Composite, 75 ohm
Minimum Illumination	2.5 Lux (Color), 0.2 Lux (B/W)
Composite Output	Yes
Micro SD Slot	Yes
Power Over Ethernet (PoE)	IEEE 802.3af compliant
Camera Control & Setup	E. Adjustments - Zoom and Focus
General Information	EC-2M-B3N
Operating Temperature	-20°F ~ 122°F
Operating Humidity	Within 90% RH
Power Consumption	14W / 1 Amp (LEDs On) 4W / 500mA (Camera Only)
Input Voltage	24VAC Voltage

*Specifications are subject to change without any prior notice.

DIMENSIONS (INCH:MM):

