

WIRELESS DAY / NIGHT BULLET CAMERA



ZX-700SR105 5.8GHz FM-LIVE 700-Line Color All-Weather IR-105' Range 6mm-22mm Varifocal Wireless CCD Camera

All New, this easy to install all weather wireless bullet camera transmits 5.8GHz, FM Live Real-Time video from **300 feet up to 4 miles** depending on optional receiver. This Rugged 700-Line, high resolution camera features a **6mm-22mm varifocal zoom lens** perfect for protecting property and assets with exceptional **night-vision ranging up to 105 Feet**.



ADVANTAGES

- 5.8GHz FM Live **Real-Time Video up to 4 Miles**
- High Intensity **Night Vision Range up to 105'**
- **Dynamic 6mm-22mm Varifocal Lens** Perfect for Extreme Wide Angle Surveillance Applications
- External On-Screen Display Menu Control for Convenient Setup & Picture Adjustments
- Universal 3-Axis Mounting Bracket for Easy Installation and Camera Positioning
- Rugged All Weather IP-66 Rated Cast Aluminum Design with Sun-Shield Hood & Anti-Glare Lens
- Free Technical Support, Application Design Assistance & 100% Performance Guarantee

APPLICATIONS INCLUDE

ZX-700SR105



HARBOUR



PARKING LOTS



CONSTRUCTION SITES



FREEWAY

SPECIFICATIONS

OPERATING FREQUENCY	5.725GHz – 5.875GHz; 8 User Selectable Channels
RADIATED POWER	50mV/m @ 3m
RANGE & ELEVATION (LINE-OF-SIGHT)	Range from 300' up to 4 Miles Depending on Optional Receiver & Antenna (Sold Separately)
ANTENNA TYPE	3dB Omni-Directional Rubber Duck
ANTENNA CONNECTOR	SMA-Female
VIDEO FORMAT	NTSC
CAMERA TYPE	1/3 Sony 960H CCD Sensor
RESOLUTION	700 Lines
CAMERA LENS TYPE	6mm-22mm Varifocal Lens
CAMERA IR RANGE	Up to 105 Feet
CAMERA MINIMUM ILLUMINATION	0.001 LUX @ F1.2
CAMERA IR CUT FILTER	Automatic / Mechanical
WDR FUNCTION	Zone Configurable Backlight Compensation
CAMERA S/N RATIO	>50dB
CAMERA SYNC / WHITE BALANCE	Automatic
VIDEO CONNECTOR	BNC-Female
VIDEO IMPEDANCE & LEVEL	75 Ohms @ 1 Volt P-P
ON SCREEN DISPLAY MENU	Adjust Exposure, White Balance, Color, Sharpness, Motion Detection ON / OFF, Privacy Masking, Monitor Mode & Dead Pixel Compensation
POWER SUPPLY INCLUDED	Yes - Model #PS-121C Class V CEC
CAMERA CURRENT CONSUMPTION	260mA @ 12VDC IR OFF / 750mA @ 12VDC IR ON
CAMERA POWER CONNECTOR	2.1mm Barrel Jack
CAMERA CONSTRUCTION	Rugged All-Weather IP-66 Rated Cast Aluminum Design
CAMERA DIMENSIONS	4" x 6" (102mm x 162mm)
CAMERA WEIGHT	3.7Lbs (1656g)
CAMERA MOUNTING BRACKET	Integrated 3-Axis Cast Aluminum Wall-Mount
OPERATING TEMPERATURE RANGE	-40°F to +170°F (-40°C to 77°C)
FCC / IC APPROVED	Yes

Specifications are Subject to Change Without Notice

KIT INCLUDES

- ALL WEATHER WIRELESS IR CAMERA
- 3dB OMNI-DIRECTIONAL RUBBER DUCK ANTENNA
- 12VDC POWER SUPPLY
- UNIVERSAL MOUNTING BRACKET
- OPERATING INSTRUCTIONS
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY

