

## HD Bullet IR Network Camera




MPIX 13 BIR - MPIX 21 BIR



## 1.3/2.1Mp CMOS HD Network Water-proof IR Mini Network Camera

### 1/3" 1.3Mp / 2.1Mp CMOS HD Mini Network Camera

- ❖ 1/3" 1.3 / 2.1 Megapixel Aptina CMOS image sensor
- ❖ Full HD 1080P (Model Specific)
- ❖ IP68 all-environments protection, 4000V Lightning Protection, constant temperature automatic control & anti-fog
- ❖ Max. IR Distance: 20m
- ❖ High-performance TI DaVinci series DSP
- ❖ H.264 & MJPEG video compression & JPEG image capture
- ❖ Dual encoding streams supported
- ❖ True Day/Night ICR
- ❖ Support DC12V power supply, PoE
- ❖ Built-in Web server, NetFLOW, WatchNET VMS
- ❖ Support Multicast



#### Model MPIX 13-BIR:

Max 30fps@720P(1280×720)  
 15fps@1.3M(1280×960) resolution  
 Lens: 3.6mm

#### Model MPIX 21-BIR:

Max 30fps@1080P resolution  
 Lens: 3.6mm

**Special order: (6mm)**




BRACK-BB-35-C BRACK-WM-35-C BRACK-PM-35-C



Professional 64 CH NetFLOW LT  
FREE Software included



iPhone



Model	MPIX - 13 BIR	MPIX - 21 BIR
<b>General</b>		
Processor	TI DaVinci Series DSP	
Operating System	Embedded LINUX	
Resource	Simultaneous remote monitoring, local recording and remote control	
User Interface	Built-in Web server, NetFLOW, WatchNET E compatible	
<b>Camera</b>		
Image Sensor	1/3" 1.3 / 2.1 Megapixel Aptina CMOS image sensor	
Effective Pixels	1280(H) × 960(V)	
Electronic Shutter	PAL Auto/Manual, 1/3~1/10000s NTSC Auto/Manual, 1/4~1/10000s	
Mini. Illumination	0.1LUX/F1.2(Color), 0.05LUX/F1.2(B/W) 0LUX(IR On)	
Signal Noise Ratio	>50dB	
Gain Control	Auto/Manual	
White Balance	Auto/Manual	
Day/Night	ICR	
Lens Mount	M12	
Lens	Fixed 3.6mm	Fixed 3.6mm (6mm optional) <b>Special order: (2.8mm, 8mm, 12mm)</b>
<b>Video</b>		
Video Compression	H.264/MJPEG	
Image Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)	2.1M1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480)
Encoding Speed	Max 30fps@720P(1280×720) 15fps@1.3M(1280×960) resolution	Max 30fps@1080P resolution
Bit Rate	128K ~ 8192Kbps	
Snapshot	Fastest 1fps JPEG capture	
Video Format	PAL / NTSC	
<b>Network</b>		
Ethernet	RJ-45 (10/100Base-T)	
Network Functions	HTTP, TCP/IP, IPv4/IPv6, ARP, IGMP, ICMP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPNP, NTP, Bonjour, SNMP, Onvif, Support Multicast	
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade	
<b>Environmental</b>		
Max. IR Distance	20m	
Ingress Protection	IP68, 4000V Lightning Protection	
Power Supply	DC12V, PoE	
Power Consumption	Max.4W	
Operating Temp./ Humidity	-35°C ~ +50°C / -31°F ~ +122°F, 10% ~ 90%	
Dimension	64.43mm x 145.02mm / 2.53" x 5.71"	

All logos & trade marks represent the registered users only. All rights reserved.  
All product specifications on this brochure are subject to change without notice.

**CANADA:**  
351 Ferrier Street, Unit 5  
Markham, ON L3R 5Z2  
Toll Free: 1-866-843-6865  
Tel: 416-410-6865  
Fax: 1-866-331-3341

**USA:**  
171 Cooper Ave. Suite 110  
Tonawanda, NY 14150 USA  
Toll Free: 1-855-404-3193  
Local: 1-716-877-7277  
Fax: 1-866-331-3341

[info@watchnetinc.com](mailto:info@watchnetinc.com)  
[www.watchnetinc.com](http://www.watchnetinc.com)

**INDIA:**  
RZ- 2, Ground Floor, Kapashera  
Opp Kapashera Police Station  
New Delhi-110037  
Tel/Fax: +91 11 26816005

**UAE:**  
P O Box 126312  
No 703, Oxford Towers  
Business Bay  
Dubai, UAE  
Tel: +971 4 2767117