

AD2I-0CH



FEATURES

- HD-TVI 2M Plastic Pancake Camera
- 1/3" Progressive scan CMOS Sensor
- HD-TVI (2M 1920×1080P)
- DNR (Digital Noise Reduction)
- Dark Hunter (×32)
- Digital Zoom (×12)
- BLC (Backlight Compensation)
- MIRROR (Horizontal)
- DEFOG

Dark Hunter



Dark Hunter (Full HD, 30fps)




IR Camera (Full HD, 30fps)



Normal Camera (Full HD, 30fps)

DIMENSIONS



Camera

Image Sensor	1/3 inch Progressive scan CMOS Sensor
Scanning System	Progressive Image Processing
Effective Pixels	1944 (H) x 1092(V)
Lens	Fixed Mega Pixel Lens(3.6mm, F 1.8)
Min. Illumination	Dark Hunter : 0.0005 Lux
BLC	ON/OFF
Exposure	AUTO / MANUAL
White Balance	ATW(2,000°K~10,000°K) / MANUAL / PUSH
Day & Night	Color
Functions	WDR, FLICKERLESS, DNR, ACE, DEFOG, PRIVACY MASK, MIRROR, BLC, MOTION
Sync. System	Internal Sync
Electronic Shutter	1/30(25) ~ 1/30,000
HD Format	TVI Output 1Vp-p, 75ohm
Horizontal Resolution	1920 x 1080P/30fps or 25fps
Analog Video	Analog Composite(1V±0.2Vp-p)
Supply Voltage	12V DC (±10%)
Power Consumption	210mA, 2.5W (Max)
Operating Temperature / Humidity	-10℃ ~ 50℃ / 30% ~ 80% RH
Storage Temperature / Humidity	-20℃ ~ 60℃ / 20% ~ 90% RH