



GOLDEN STATE INSTRUMENT CO.

GS-3600WDC

**1/3" HIGH RESOLUTION DSP COLOR
WIDE DYNAMIC CAMERA**

- 1/3" Double Speed Color CCD With 410K Pixels.
- Enhanced WDR Function Max 56 dB.
- SDNR (Super Dynamic Noise Reduction).
- 0.05 Lux at F1.2 (AGC ON).
- 0.001 Lux at F1.2 (Sens-up Mode).
- S/N Ratio 50dB (Mini).
- Privacy Image Masking With Free Position.
- RS 485 Remote Control.
- Multi Language (ENG / JAN / CN).
- OSD (On Screen Display).



Specification:

Model No.		GS-3600WDC
TV System		NTSC / PAL
IMAGE SENSOR		1/3-inch CCD Image Sensor
CCD Total Pixels		811(H) X 508(V) / 795(H) X 596(V)
Scanning System		525 lines, 60 fields/sec / 625 lines, 50 fields/sec
Sync system		Internal / Line-Lock
Minimum Illumination	Typical	0.05 Lux (F1.2 , 5600°K)
	Star Light Mode	0.001 Lux (F 1.2 , 5600°K)
Resolution		520 TVL (Color), 570 TVL (B/W)
White Balance	Mode	ATW / AWB / FIX
	Range	3200 ~ 10000 °K
Gamma Correction	Mode	AGC (ON / OFF)
	Range	0 ~ 18dB
S/N Ratio		56dB (Max) / 50dB (MIN)
AUTO IRIS		A.E.S. / DC
OSD Display		ON SCREEN DISPLAY FOR ALL CONTROL
5 PUSH SW		FOR OSD CONTROL PANEL
UP Side Down		SELECTABLE BY OSD MANUAL
B.L.C. Function		SELECTABLE BY OSD MANUAL
Digital Zoom (X2)		SELECTABLE BY OSD MANUAL
ALARM OUT		Motion Detect
RS-485 I/F		DIM connector
WIDE DYNAMIC		52dB (MAX)
Video Output		Composite & Y/C output 1.0Vp-p at 75 ohm
GAMMA CORRECTION		0.45 / 1.0 (SELECTABLE BY OSD MANUAL)
Power Supply		DC12V & AC24V / 6W

14256 Doolittle Drive · San Leandro, CA 94577 · 1-800-227-2330 · Fax(510)352-5988

Website: www.goldenstateinst.com · E-mail: gsi@goldenstateinst.com