



## Color License Plate Capture Camera

### IV-LP1616

#### Features:

- 1/3" Sony Super HAD II Hi-Res CCD
- 540TVL (Color) / 600 TVL (B/W) 9~22mm Lens
- 36pc IR LED
- 50 ft (15m) IR Range
- Up to 16 MPH (30 KPH) Capture Speed
- IP 66 Protection
- Power Supply: 24VAC/12VDC, Dual Voltage



| Specification          | IV-LP1616                                                                   |
|------------------------|-----------------------------------------------------------------------------|
| Image Sensor           | 1/3" Sony CCD                                                               |
| Effective Pixels (HxV) | NTSC: 768x494, PAL: 752x582                                                 |
| Horizontal Resolution  | 540TVL Day, 600TVL Night                                                    |
| IR LED                 | 36pcs LED                                                                   |
| IR Range               | 15m distance (50ft)                                                         |
| Minimum Illumination   | 0.015 Lux (Day Light), 0.0 Lux (w/IR LED on) Sensitivity D/N More than 50dB |
| S/N Ratio              | More than 50dB                                                              |
| Lens                   | 9~22mm                                                                      |
| Day/Night              | Yes (Mechanical ICR Filter)                                                 |
| Capture Range          | 3~8m (10-27ft)                                                              |
| Capture Speed          | up to 16MPH                                                                 |
| White Balance          | Auto                                                                        |
| BLC                    | Auto (Center Weighting)                                                     |
| Video Output           | 1VP-P, 75 Ohms                                                              |
| Power Supply           | AC 24V / DC 12V                                                             |
| Power Consumption      | 10W/10W max                                                                 |
| Ingress Protection     | IP66                                                                        |
| Dimensions (LxWxH)     | 3.26" x 8.09" (83mm x 205mm)                                                |
| Storage Temperature    | -4°F ~ 140°F (-20°C~+60°C)                                                  |
| Operation Temperature  | 14°F ~ 122°F (-10°C~+50°)                                                   |
| Weight                 | 1.35 lbs.                                                                   |