


## Full HD Speed Dome IP Camera

- 360° Endless Pan Travel
- Quad Stream Support
- Dual Streams, Full HD real-time + D1 real-time
- Quad Stream Compression:
  - H.264 Baseline / Main / High Profile + MJPEG
- Vertical View mode (Image rotation by 90°)
- 20x optical zoom
- Up to 8x digital zoom
- Wide Dynamic Range
- Auto White Balance
- AGC Control
- Backlight Compensation
- Auto Exposure
- True Day/Night function with IR Cut Filter
- Digital Noise Reduction
- Network Failure Detection
- Digital Slow Shutter




## Dimension Diagram

IN-DI2MPTZ20X



IN-DO2MPTZ20X



## Popular Mounting Solutions

Surface	Accessories not required
Wall	IN-XMPM OR IN-XSPM 
Pendant	IN-XIMK OR IN-XST2  Only required for IN-DI2MPTZ20X
Corner	IN-XIMK OR IN-XCST  Only required for IN-DI2MPTZ20X
Pole	IN-XIMK OR IN-XPTD  Only required for IN-DI2MPTZ20X
Flush	IN-X0720 
Parapet	IN-XPMAQ 

# IN-DI2MPTZ20X IN-DO2MPTZ20X

## Product Specifications

Item	IN-DI2MPTZ20X	IN-DO2MPTZ20X
	Indoor	Outdoor
<b>● Camera</b>		
Image Sensor	1/2.8" Sony Progressive CMOS	
Optical Zoom	20x	
Digital Zoom	1 ~ 8x variable	
Minimum illumination	0.05 (Color), 0.01 lux (B/W) @ F1.6	
Focal Length	4.7 ~ 94 mm	
Focus Mode	Auto / Manual	
White Balance	Auto / Indoor / Outdoor / ATW / Manual	
Iris Control	Auto / Manual	
Electronic Shutter	1/1 ~ 1/10k sec.	
AGC Control	Auto / Manual	
Backlight Compensation	On / Off	
<b>● Operation</b>		
Pan Travel	360° endless	
Tilt Travel	-10° ~ 190°	
Manual Speed	0.5° ~ 90°/s	
Presets	256	
Preset Accuracy	0.225°	
Preset Speed	5° ~ 400°/s	
Sequence	8	
Auto Pan	4	
Cruise	8	
Privacy Mask	16	
Proportional Pan & Tilt	On / Off (Pan and tilt speed proportional to zoom ratio)	
Resume after Power Loss	Yes	
Home Function	Preset / Sequence / Auto Pan / Cruise	
Auto Flip	Image / Mechanical / Off	
Motion Detection	On / Off	
Wide Dynamic Range	On / Off	
Day/Night: IR Cut Filter	Auto / Manual	
Image Rotation	Flip / Mirror / Inverse / Portrait	
Digital Noise Reduction	On / Off	
<b>● Network</b>		
Video Compression	H.264 / MJPEG	
Video Streaming	Quad Streams H.264 x4 / H.264 x3 + MJPEG	
Video Resolution	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF	
Frame Rate	1080P (30 fps) + D1 (30 fps)	
Audio Compression	G.711 / G.726 ADPCM / AAC	
Audio Streaming	Two-way Audio	
Networking	10/100 Mb Ethernet (RJ-45)	
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, IEEE 802.1x, QoS, ONVIF	
Security	User Account and Password Protection	
Alarm	Input	4 Sets
	Output	2 Sets
Alarm Reaction	Preset / Sequence / Auto Pan / Cruise	
Micro SD	Micro SDHC 32GB support	
Internet Browser	Internet Explore (6.0+) / Chrome / Firefox / Safari	
<b>● General</b>		
Environment	Indoor	Outdoor
Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)	-40 °C - 50 °C (-40 °F ~ 122 °F)
Dimension	Ø 171.7 x 228.71 mm (Ø 6.76 x 9 inches)	Ø 191.97 x 282.11 mm (Ø 7.55 x 11.1 inches.) w/ Sunshield
Weight	1.62 Kg (3.57 lbs)	2.32 Kg (5.11 lbs)
Power Source (not included)	PoE+ / AC 24V ± 10%	PoE+ (w/o Heater) / AC 24V ± 10%
Power Consumption	20 W	65 W (w/ Heater)
Regulatory	CE / FCC / RoHS	CE / FCC / RoHS / IP66

\* All specifications are subject to change without notice.

\* All brand names and registered trademarks are the property of their respective owners.