



Indoor Dome Camera

IV-502V

Features:

1/3" SONY Super HAD CCD
 Day/Night Function
 600 TVL
 0.3 Lux (Color)/ 0.03 Lux (B/W)
 On Screen Display Menu
 Mirror
 Privacy Zone
 Motion Detection
 3-Axis



SPECIFICATION	IV-502V
Resolution	600 TVL
Sensor	1/3" SONY Super HAD CCD
Total Pixels	NTSC: 811(H)x508(V) 410k Pixels
Effective Pixels	NTSC 768(H)x494(V) 380k Pixels
Scanning System	2:1 Interface
Synchronization	Internal
Frequency	NTSC:Horizontal15.734kHz/ Vertical: 59.94Hz
S/N	More than 50dB (AGC Off)
Video Output	CVBS 1.0Vp-p/75ohm
Min. Illumination	0.3 Lux (Color) @ F1.2 / 0.03 Lux (B/W)
White Balance	ATW/ ATC/ Manual (2100k ~ 10500k)
ES Speed	Auto/Manual (NTSC:1/60sec~1/120000sec)
Lens	2.8-12mm
O.S.D	Built-In
Backlight Compensation	On/ Off
Gain Control	On/ Off
Day/Night	Auto/On
Motion Detection	On/ Off, 64 Grids
Privacy Zone	On/ Off, 4 Zones
Mirror	On/ Off
Operating Temp.	14F~122F/-10C~50C / 30%~80% RH
Storage Temp.	-4F~140F/-10C~50C / 20%~90% RH
Power	DC 12V/AC 24V