



## 21 LEDs Hi-Res IR Dome Camera

### IV-DIR133C

#### Features:

- . High resolution for clearer and sharper images
- . High sensitivity in the dark environment, 0.4Lux / F2.0, 0Lux (IR ON)
- . Day and night features for 24-hour surveillance
- . IR LED effective range reaches up to 45 feet



SPECIFICATION*	IV-DIR133C
Pick up Element	1/3" H.R. color CCD image sensor
Number of Pixel	771(H) x 492(V) <NTSC> / 753(H) x 582(V) <PAL>
Resolution	500 TV Lines
Min. Illumination	0.4Lux / F2.0, 0Lux (IR ON)
IR LED	21 units
Effective Range	Up to 45 feet
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
IRIS Mode	AES
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Power Source (±10%)	DC12V
Current Consumption (±10%)	90mA (IR OFF), 210mA (IR ON)
Dimensions (inch)**	3.68"(Ø) x 2.8"(H)

\* The specifications are subject to change without notice.

\*\* Dimensional Tolerance: ± 3/16"