

5 Mega Pixel Network Outdoor Dome Camera



Description:

The CDI5112VIR outdoor dome camera provides high quality video at 5.0 mega pixel resolution. The infrared LEDs provide illumination for clear image quality at night. The IP66 weatherproof rating makes this dome camera suitable for outdoor applications such as gas stations, retail parking lots and many others. Costar Video's IP cameras are compatible with the iNEX user interface platform. The iNEX user interface incorporates features such as simplified user management, advanced camera mapping and logical camera grouping making it easier to monitor and access each of your cameras. The iNEX user interface also has the ability to integrate both analog and IP camera technology on the same platform allowing you to have a diverse surveillance system. Costar Video's IP cameras are OnVIF supported. The industry standard OnVIF protocol that makes it easy to integrate Costar branded IP cameras with OnVIF compatible recorders.

Features:

- 5 mega pixel resolution
- 3.3-12 mm vari-focal DC auto iris IR corrected lens
- 1/2.5" Aptina CMOS image sensor
- 25 pcs Super Flux IR LEDs
- 65 – 82 feet (20 – 25 meters) IR distance
- True day/night with IR cut filter
- OnVIF supported; iNEX compatible
- SD memory card supported
- Black Light Compensation (BLC)
- 3D Digital Noise Reduction (3DNR)
- Multiple compression (H.264, MJPEG)
- Dual IP streaming
- Cross web-browsing
- Dynamic adjustment bit rate
- Weatherproof IP66 rated
- Power over Ethernet (PoE) or DC12V



CDI5112VIR Specifications

Model	Lens (mm)	Resolution
CDI5112VIR	3.3-12 mm	5 Mega Pixel

Power	
Source	DC12V or PoE
PoE	802.3af
Sensor	
Image Sensor	1/2.5" Aptina CMOS
Lens	3.3-12 mm Auto Iris Vari-focal IR Corrected
Minimum Illumination	0.5 Lux @ F1.2 (Color) 0.0 Lux (IR LED On)
Resolution	2592 x 1920
Frame Rate	Up to 10 fps
Field of View	79.3°~29.8°
IR LED	25 pcs 850 nm Super Flux High Powered LEDs
IR Distance	65 - 82 feet (20 - 25 meters)
Electronic Shutter	1/5 – 1/50,000 50/60Hz
Video Features	
Compression	H.264, MJPEG
Streaming	Multi Stream
Standards	OnVIF
Bit Rate	Stream1; 50Kbps-12Mbps Stream2; 10Kbps-6Mbps Stream3; MJPEG fixed
Quality Setting	1 – 9 (9 = Highest)
Brightness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102db
Camera Functions	
BLC	Yes
DNR	Yes; 3D
Masking	Yes; 5 user defined areas < 8% of total picture

Network	
Ethernet	1 (10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4 / IPv6 (DHCP/Fixed)
Compliance	OnVIF v22 (Profile S)
Supported Protocols	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP, Unicast and multicast supported

General Information	
Temperature	14°F to 131°F (-10°C to 55°C)
Humidity	85% RH Max
Approvals	FCC, CE, RoHS, IP66, IK10
Dimensions	5.1" x 4.4" (130 x 112 mm)
Weight	1.87 lbs. (0.85 kg)

Applications	
	<p>iNEX Connect and manage IP and Analog cameras onto a single user interface.</p>

Costar
VIDEO SYSTEMS

101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com

Specifications and design are subject to change without notice. Conversions: 1" = 25.4mm Measurement conversions are approximate.