

DATA SHEET

Vandal Dome : Fixed Day/Night IR | 480 TVL

ice



HIGH RESOLUTION IMAGE CAPTURE

MODEL: CAM/VDN4IR/A



FEATURES

- Specially designed for challenging 24-hour surveillance applications
- Day & Night mode: Color converts to B/W in low light with an IR cut filter removal (ICR) function
- 1/3" Interline Transfer Sony CCD™
- Outstanding night vision 0 lux with IR
- High impact, vandal resistant rugged dome camera
- Advanced high image quality
- Power input transient polarity protection
- 4-9mm F1.6-2.4 varifocal lens
- Interior/Exterior application (Weatherproof - IP66 Rated)
- Dual power operation 12v DC / 24v AC auto switchable
- Easy to install and configure
- 3 Year Advanced Replacement Warranty



SPECIFICATION

CAM/VDN4IR/A (NTSC)		
Camera Features	Lens	4-9mm, F1.6-2.4 Varifocal
	Resolution	480 TVL
	Image Sensor	1/3" Interline transfer SONY CCD
	Scanning System	2:1 interlace
	Scanning Frequency	15.734KHz(H), 59.94Hz(V)
	Sync System	Internal / Line Lock
	Electronic Shutter	1/60 ~ 1/100,000 sec
	Minimum Illumination	0.8 lux (color), 0.08 lux (B/W) @ F1.2, 50 IRE 0 lux IR LED ON
	Video Output Level	BNC connector
	Signal to Noise Ratio	50dB (AGC off)
	Unit Cell Size	6.35 (H) x 508(V)
	Picture Element	811(H) x 508(V)
IR	BLC	40% Center
	IR LED	23 pcs (2 Sensor) high brightness IR LED
	IR Wavelength	850nm
	IR Range	25m~30m (from object of view reflected infrared)
Power Supply	IR Project Angle	40°
	Power Source	12v DC / 24v AC
Mechanical	Power Consumption	Max 3.5 Watts / 6.85 Watts (IR ON)
	Power Input	2-pin wire
	Video Output	BNC connector
	Lens Mount	Fixed mount
	Dimensions (DxH)	5.1" x 3.9" (130mm x 100mm)
Environmental	Weight	1.8 lbs (800g)
	Operating Temperature	14° ~ 122°F (-10°~50°C) (optional heater -22° ~ 122°F)
Warranty		
3 Year Advanced Replacement		



PRODUCT CODES*

VANDAL DOME : FIXED DAY/NIGHT IR | 480 TVL
VANDAL DOME WALL/CEILING MOUNT AND BRACKET
VANDAL DOME HEATER

CAM/VDN4IR/A
CAM/VDABI/A
CAM/VFDHT202V

* SEE OUR WEBSITE FOR FULL ACCESSORIES LISTING

ACCESSORY NOTE: CAM/VDABI/A can accomodate CAM/SDAPM/A (pole) or CAM/SDACM/A (corner) mount brackets

PLEASE CHECK THE WEBSITE OR YOUR LOCAL REPRESENTATIVE FOR PRODUCT ORDERING INFORMATION AND OTHER DEVELOPMENTS

www.dedicatedmicrosinc.com

Dedicated Micros USA

14434 Albemarle Point Place, Suite 100, Chantilly, Virginia 20151 USA Toll Free : 800 864-7539 Tel: +1 703 904-7738 Fax: +1 703 904-7743

Dedicated Micros Canada

5580 Explorer Drive, Suite 501, Mississauga, Ontario L4W 4Y1 Tel: +1 905 602-6222 Fax: +1 905 602-6221

The manufacturer reserves the right to change the specification without notice. All trademarks are courtesy of registered owners.

The DM logo is a trademark of Dedicated Microcomputers Group Ltd. NetVu Connected is a trademark of the AD group.