

**IP66 CERTIFIED** 

LOW PROFILE



WHITE






RED



GREEN






















# **Summary**


The MC355T is a high performance micro dome camera that offers exceptional Wide Dynamic Range and sensitivity for harsh lighting environments, and innovative features in a sleek, attractive design. This compact camera utilizes a 1/3" PIXIM Seawolf CMOS sensor. PIXIM's technology allows each pixel to self-adjust in the same scene, giving terrific image quality. PIXIM revolutionizes the way video cameras capture and process images. This camera is NEMA rated IP66 with shock resistant aluminum housing and offers colorful accessories for the final decorative touch. This camera is perfect for any application where esthetics and low profile are vital.

#### **Features**

- 1/3" SHARP CCD
- 480TV Lines [Color], 520TV Lines [B/W]
- 3.6mm Fixed Iris Lens
- Low Power Consumption (Max 0.7W)
- TDN (True Day/Nigh with IR Cut Filter)
- Enhanced Sensitivity 0.4 Lux F1.2
- 3D Gimbal for Easy Control
- Ultra Low Light Sensitivity
- Wide Operating Voltage (8VDC~18VDC)
- IP66 Certified
- 5 Year Warranty

## Dimensions (unit: mm)





### **Specifications**

VIDEO	
mage Sensor	1/3" PIXIM CMOS
Total Pixels	742 (H) x 552 (V),
Effective Pixels	720 (H) x 540 (V)
Lens	3.6mm Fixed Iris Lens
Frequency	15.734KHz (H), 59.95Hz (V)
Video Output	VBS 1.0Vp-P (75 Load)
Horizontal Resolution	480TV Lines [Color], 520TV Lines [B/W]
Minimum Illumination	F1.2 (30IRE): 0.08 Lux [Color]
	F1.2 (30IRE): 0.01 Lux [B&W]
S/N Ratio	45dB
Video Output	CVBS: 1.0Vp-p / 75 Ω
ENVIRONMENTAL	
Operating Temperature	-10oC ~ 55oC (14oF ~ 131oF)
Operating Humidity	Less than 90% (Non-Condensing)
Storage Temperature	-20oC ~ 70oC (-4oF ~ 158oF)
ELECTRICAL	
Power Requirement	12VDC
Power Consumption	Max 1.5 Watt
MECHANICAL	
Housing Material	Aluminum
Dimensions	80 X 59.5mm (3.15x 2.34 in)
Weight	0.562 lbs (255g)

\*Specification is subject to change without prior notice.

# Accessories (Optional)




DWC-MCSM Surface Mount Bracke



Trim Ring (Red Color)



Trim Ring (Green Color)



DWC-MCAM Micro Dome Angle Mount Bracket



DWC-MC BLU

Trim Ring (BlueColor)



DWC-MC BLK Trim Ring (BlackColor)

