

EHD362

Outdoor 3-Axis IR Dome Camera

The EHD362 is an outdoor, vandal resistant 3-axis IR dome camera which utilizes a Sony 1/3" Super HAD CCD Sensor to provide high resolution 540TVL color video for security surveillance applications. Vandal Proof materials and an IP66 weather resistant housing allow reliable operation in outdoor and indoor environments.

True day/night operation combined with 25m (~80ft.) range high efficiency IR LEDs makes the EHD362 suitable for a wide range of day and night surveillance situations. Plus, the 3-axis mechanical design, built-in f=3.7~12mm varifocal auto iris lens and dual voltage (12VDC/24VAC) operation bring flexibility to installation and field of view adjustment.

Features

- Color dome camera with SONY 1/3" Super HAD CCD sensor.
- High resolution 540 TVL
- 3-Axis design for flexible positioning.
- · High sensitivity, low smear, high antiblooming and high S/N ratio.
- Built-in Auto Gain Control (AGC), Auto Tracking White Balance (ATW).
- Built-in 3.7~12mm varifocal DC-drive auto iris lens.
- 25m (~80ft.) range IR-LEDs
- True day/night auto switching with IR filter removal for B/W images in low light environments.
- Vandal proof to withstand impact of a 10 pound sledgehammer
- Dual voltage 12VDC/24VAC operation
- · Weather resistant, IP66 rated.

Pickup Device	1/3" SONY Super HAD CCD Sensor
Video Format	NTSC
Picture Elements	768 x 494 (NTSC), 752 x 582 (PAL)
Horizontal Resolution	540 TVL
Sensitivity	0.12 LUX / F1.6 ; 0 LUX (IR LED ON)
S/N Ratio	Over 48dB (AGC off)
Electronic Shutter	1/60(1/50)s~1/100,000s
Video Output	BNC 1.0Vp-p 75Ω
Gamma Correction	0.45
Lens Type	Vari-Focal 3.7~12mm F1.4 DC Drive Auto Iris Lens
Day/Night	True day/night with motorized IR cut filter
Gain Control	Automatic
White Balance	ATW (2500°K~9500°K)
Sync. Mode	Internal Sync.
IR LED	11 Units High Efficiency IR LED
IR Wavelength	850nm
IR Distance	25m (~80ft.) nominal; depends on environment
Weather Resistant	IP 66
Vandal Proof	Yes
Power Source	12VDC/24VAC
Power Consumption	283mA @12VDC, 335mA @ 24VAC
Operating Temp	-10°C~50°C / 14°F~122°F
Dimensions (O.D. x H)	142mm x 115.5mm / 5.6" x 4.55"
Weight	979 g / 2.16 lbs
Certifications	CE / FCC

Ordering Information

EHD362: Color Outdoor 3-Axis IR Dome Camera, NTSC, f=3.7~12mm, Dual voltage, NTSC