



## Kits & Housings

Indoor/Outdoor 6" Pendant Dome Housing

# **Dome6 Series**

High quality environmental housing designed for the MP8P and MP8D-L4 cameras. Combining this 6" dome with the superior imaging of a megapixel dome camera provides the perfect solution for environments in which cameras need to be less noticeable or require additional protection from the elements

#### **Features:**

- Indoor or outdoor applications
- Heavy duty enclosure features an IP66 rating for applications in harsh environments
- Full view in all directions: for use with the MP8P 180° view or MP8D-L4 360° view panoramic camera to ensure outstanding observation with excellent color sensitivity and high resolution
- Wall mount or pendant mount
- Easy installation and superior design suitable for mutiple applications







# **Dome6 Series**


# Indoor/Outdoor 6" Pendant Dome Housing

Models		
Dome6-I-C	Indoor 6" Vandal Resistant Top Mount Version	
Dome6-I-W	Indoor 6" Vandal Resistant Wall Mount Version	
Dome6-O-CH	Outdoor 6" Vandal Resistant Top Mount Version - with Heater, Blower and Sunshade	
Dome6-O-WH	Outdoor 6" Vandal Resistant Wall Mount Version - with Heater, Blower and Sunshade	

### Mounting Options







**Top Mount** 

#### Specifications

Mechanical	Housing Material	Aluminum
	Dome Cover Protection	Vandal Resistant Polycarbonate
	Color	Gray
Ho	Dome Diameter	6" (Indoor/Outdoor)
	Housing Height	Indoor: 6.3" (160mm)
		Outdoor: 6.4" (162mm)
	Housing Diameter	Indoor: 8.6" (218mm)
		Outdoor: 9.3" (236mm)
	Weight w/o Camera	Indoor Housing: 1.3 lbs
		Outdoor Housing: 1.3 lbs
		Pendant Bracket: 1.5 lbs
		Wall Mount Bracket: 2.2 lbs
Electrical	Power Supply	Indoor: Not Applicable
		Outdoor: 24 VAC Heater/blower .8A
	Power Consumption	Indoor: Not Applicable
		Outdoor: 20 Watts Maximum
Environmental	Operating Temperature	Indoor: 32°F to 122°F
		Outdoor: -40°F to 122°F
	Humidity	0 to 95% Relative, Non-condensing
	Enclosure Protection	Indoor: Not Applicable
		Outdoor: IP66 Outdoor protection grade
	Fan	Indoor: Not Applicable
		Outdoor: Operates continuously
	Heater	Indoor: Not Applicable
		Outdoor: Auto starts when temperature drops below 41°F

All specifications are subject to change without notice

