

Ikegami

ICD-E11

CCD Powered Color
Elevator Camera

High Resolution, 6 IR, Vandal Resistant Camera, IP66,
Day/Night, 2.97mm Fixed Lens, 0.0 lux, Corner Mount



FEATURES

- 1/3" Format CCD Color Elevator Camera, High Resolution, 2.97mm Fixed Lens.
- Features True Day & Night, Smart IR's, D-WDR & Weather and Tamperproof.
- Camera sees in 0 lux illumination!

Specifications:

Image Sensor	1/3" Sony High Resolution Super HADII CCD
Lens Mount	2.97mm Fixed Board Lens
Resolution	>630 TV Lines Color
Effective Pixels	NTSC: 768(H) x 494(V) PAL: 752(H) x 582(V)
Synchronizing System	Internal
Scanning System	2:1 Interlace
Frequency	NTSC: Horizontal:15.734KHz Vertical: 59.94Hz PAL: Horizontal :15.625KHz Vertical : 50.00Hz
Video Output	1.0 Vp-p Composite Signal 75 ohms
AGC	ON
Signal to Noise Ratio	52dB or more (AGC OFF)
Minimum Illumination	0 Lux for Infrared Lighting Conditions
White Balance	ATW
Electronic Shutter Speed	NTSC: 1/60s - 1/100,000s PAL: 1/50s - 1/1000,000s
Back Light	OFF
3D-DNR	ON
D&N Selection	EXT
BLC	OFF
D-WDR	OFF
HLM	OFF
Defect Pixel Compensation	OFF
IR SMART	OFF
Motion Detection	OFF
Privacy Masking	OFF
Mirror	OFF
Sharpness	OFF
IR LEDs	6 IR LEDs
Power Supply Consumption	DC12V 110mA CDS ON : 170mA
Operation Temperature Humidity	-10°C~+50°C 0~80% RH
Weight	Approx. 320g
Dimensions	120(H) x 120(W) x 90(D)mm

Design and specifications are subject to Change without notice.

IKEGAMI ELECTRONICS, (U.S.A.) INC.

URL: <http://www.ikegami.com> email: cctv@ikegami.com

Headquarters

West Coast

South West

South East

Midwest

37 Brook Avenue, Maywood, NJ 07607 Phone (201)368-9171 Fax (201)569-1626

Redondo Beach, CA 90278 Ph (310)297-1900 Fax (310)536-9550

Waxahachie, TX 75167 Ph (972)869-2363 Fax (972)556-1057

Deerfield Beach, FL 33441 Ph (954)571-7177 Fax (954)571-7760

Bloomingdale, IL 60108 Ph (603)-372-8777 Fax (603)-372-8777