

<b>AV2225PMIR</b>	<b>1080p Full HD H.264 IP MegaView® 2 camera with 3-9mm Remote Zoom, Remote Focus, P-Iris Lens and IR Illuminator</b>
<b>AV2225PMTIR</b>	<b>1080p Full HD H.264 IP MegaView® 2 camera with 8-22mm Remote Zoom, Remote Focus, P-Iris Lens and IR Illuminator</b>
<b>AV2225PMIR-S</b>	<b>1080p Full HD H.264 IP MegaView® 2 camera with 3-9mm Remote Zoom, Remote Focus, P-Iris Lens, IR Illuminator and SDHC card</b>
<b>AV2225PMTIR-S</b>	<b>1080p Full HD H.264 IP MegaView® 2 camera with 8-22mm Remote Zoom, Remote Focus, P-Iris Lens, IR Illuminator and SDHC card</b>
<b>AV2225PMIR-SA</b>	<b>1080p Full HD H.264 IP MegaView® 2 camera with 3-9mm Remote Zoom, Remote Focus, P-Iris Lens, IR Illuminator, Audio and SDHC card</b>

This A&E specification is written according to Construction Specifications Institute (CSI) 3-Part Format, based on MasterFormat™ (2009 Edition) and The Project Resource Manual – CSI Manual of Practice. [www.csinet.org/masterformat](http://www.csinet.org/masterformat).  
 Manufacturer is responsible for the accuracy of the technical data included in this specification.

## Division 28 – Electric Safety and Security

### Section 28.23.29 – Video Surveillance – Remote Devices and Sensors

#### Part 1 General

##### 1.1 General Requirements

The camera shall be of manufacturer's official product line, designed for continuous commercial or industrial use. The camera shall be based on standard parts and components and utilize proven technology using open and published protocols.

All camera installation, configuration, setup, programming and all related work shall be performed by electronic technicians thoroughly trained in the installation and service of the equipment provided and in complete compliance with all local codes and regulations.

All equipment provided shall be backed by a three-year manufacturer warranty.

##### 1.2 Certifications and Standards

- a) European Community Directives:
  - 2004/108/EC (EMC Directive);
  - 2006/95/EC (Low Voltage Directive);
  - 2011/65/EU (RoHS Directive)
  - 1907/2006/EC (REACH Directive)
  - 2002/96/EC (WEEE Directive)
- b) European EMC Standards to which conformity is declared:
  - EN 55022:2010 Class A
  - EN 55024:2010
  - EN 61000-3-2:2006+A1:2009+A2:2009
  - EN61000-3-3: 2008
  - EN60950-1:2006+A11:2009+A1:2010+A12:2011



- c) FCC Standard Compliance:  
Title 47, Part 15 (47 CFR 15) Subpart B Class A
- d) Mechanical Standards:  
ANSI/IEC 60529-2004 - IP66 dust/water Ingress protection rating
- e) Video Compression Technology  
H.264 MPEG-4, Part 10 ISO/IEC 14496-10 AVC
- f) Networking Standard:  
IEEE 802.3af-2003 PoE Standard, Class 0  
IPv4
- g) Interoperability Standard  
ONVIF Profile S and PSIA compliant
- h) Country of Origin  
FTC "Made in USA" standard compliant

## Part 2 Products

### 2.1 Manufacturer

**Arecont Vision, LLC**  
**425 E. Colorado St. #700**  
**Glendale, CA 91205**  
**Phone: 818-937-0700**  
**877-226-3728**  
**Fax: 818-937-0464**  
**[www.arecontvision.com](http://www.arecontvision.com)**

### 2.2 General

The AV2225 MegaView® 2 series network camera is part of Arecont Vision's full line of H.264 MegaView® cameras. This fully compliant implementation of H.264 (MPEG 4, Part 10) provides 1920x1080 megapixel resolution at full video frame rates of 31 frames per second (fps). The AV2225 camera line provides an all-in-one solution with integrated 1080p full HD camera, IR illuminator, remote focus, remote zoom, p-iris IR corrected wide angle or telephoto lens, SDHC card (-S model) and vandal resistant aluminum cylindrical (Bullet-style) enclosure with IP66 weatherproofing standard.

With the features of CorridorView™ for 90°, 180° and 270° image rotation(-S models), scaling (-S model), ONVIF Profile S and PSIA compliance, Casino Mode™, privacy mask, extended motion detection and flexible cropping, the AV2225 is a high sensitivity, PoE (IEEE 802.3af) compliant true Day/Night camera w/ IR illuminator. Built with Arecont Vision's massively-parallel MegaVideo® processing technology, this camera offers more than 6-times the resolution of standard resolution IP cameras with the ability to output full real-time frame rates and deliver high-quality megapixel imaging for indoor and outdoor applications.

## 2.3 Hardware

- The camera shall utilize a high sensitivity 2.07 megapixel CMOS sensor with 1/2.7" optical format, 3um x 3um pixel size, progressive scan and Active Pixel Count: 1920(H) x 1080(V) pixel array (PMIR and PMTIR model)
- The camera shall utilize a high sensitivity 2.07 megapixel CMOS sensor with 1/3" optical format, 2.2um x 2.2um pixel size, progressive scan and Active Pixel Count: 1920(H) x 1080(V) pixel array (-S model)
- The camera shall have and integrated 3-9mm,  $\Phi$ 14mm Mount, megapixel IR corrected vari-focal lens with 1/2.7" optical format, F1.2 and Horizontal Field of View of 115°-37°. (PMIR model)
- The camera shall have and integrated 8-22mm,  $\Phi$ 14mm Mount, megapixel IR corrected vari-focal lens with 1/2.7" optical format, F1.6 and Horizontal Field of View of 42°-16°. (PMTIR model)
- The camera shall have and integrated 3-9mm,  $\Phi$ 14mm Mount, megapixel IR corrected vari-focal lens with 1/3" optical format, F1.2 and Horizontal Field of View of 82°-27°. (PMIR-S model)
- The camera shall have and integrated 8-22mm,  $\Phi$ 14mm Mount, megapixel IR corrected vari-focal lens with 1/3" optical format, F1.6 and Horizontal Field of View of 26°-11°. (PMTIR-S model)
- The camera shall have a 3-axis easily adjustable bracket with 360° pan 90° tilt and 180° rotation for easy and accurate positioning.
- The camera shall have vandal resistant aluminum cylindrical (Bullet-style) enclosure with IP66 weatherproofing standard.
- The camera's power source shall be Power over Ethernet (PoE) complying with the IEEE 802.3af standard to support IR illuminator, blower and camera.
- The camera shall have an auxiliary power input, AC24V and DC12-48V, to support IR illuminator, blower and camera.
- The camera shall be utilized for indoor and outdoor applications.
- The camera shall have SDHC card slot for onboard storage up to 32GB, class 10 and UHS-1. (-S models).

## 2.4 Imaging

- The camera shall have dual standard compression support with simultaneous streaming of both H.264 and MJPEG formats.
- The camera shall feature automatic exposure, automatic multi-matrix white balance, shutter speed control to minimize motion blur, programmable resolution, brightness, saturation, gamma, sharpness and tint.
- The camera's shutter speed shall be 1ms - 500ms.
- The camera shall feature selectable 50/60 Hz flicker control, windowing, simultaneous delivery of full-field view and zoomed images at video frame rate, instantaneous electronic zoom, pan and tilt, and electronic image rotation by 180 degrees.
- The camera shall have CorridorView™ with 90°, 180° and 270° image rotation options (-S models)The camera shall have multi-streaming support of up to 8 non-identical concurrent streams (different frame rate, bit rate, resolution, quality, and compression format).
- The camera shall have dynamic range up to 69 dB and a maximum SNR of 45 dB
- The camera shall have dynamic range up to 69.5 dB and a maximum SNR of 44 dB (-S models)
- The camera shall have privacy masking, the ability to select multiple regions of an arbitrary shape to block the video.
- The camera shall have Real Time Streaming Protocol (RTSP) support allowing for compatibility with media players such as Apple QuickTime, VLC Player and others.
- The camera shall have Casino Mode to maintain 30fps or higher under any condition.
- The camera shall have extended motion detection grid, a higher granularity grid of 1024 distinct motion detection zones. User can select between 64 zone based motion detection and extended motion detection to provide backward compatibility with the existing Video Management System (VMS) integration.

- The camera shall feature streaming of the full field of view (FOV) and simultaneous multiple regions of interest (ROI) for forensic zooming.
- The camera shall provide 21 levels of compression quality for optimal viewing and archiving.
- The cameras H.264 implementation shall maintain full real time video frame rates.
- The camera shall output at a maximum resolution of 1920(H) x 1080(V) pixels up to frame rate of 31 frames per second (FPS).
- It shall be possible to program the camera to output a variety of lower resolution image and increase frame rate, i.e. 1280(H) x 1024(V) pixels at 42 FPS.
- The camera shall provide flexible cropping (Resolution windowing down to 1x1 pixels for JPEG and 2x2 pixels for H.264)
- The camera shall be able to save bandwidth & storage by running at 1/4 full resolution
- The camera shall be able to have below scaled resolutions: 720p, XGA, DVGA (16:9), DVGA (3:2), SVGA, D1 (PAL), 4CIF (NTSC), VGA, 2CIF (PAL), HVGA (4:3), 2CIF (NTSC), HVGA (8:3), HVGA (3:2), HVGA (16:9), CIF (PAL), CIF (NTSC), QVGA (SIF), QCIF (PAL), QCIF (NTSC) and SQCIF. (-S models)
- The camera shall have an Auto Exposure (AE), Gain Control (AGC), Bit Rate and Bandwidth Limit Control
- The camera shall feature MoonLight™ mode - extended exposure and noise cancellation
- The camera shall be able to support Picture-in-Picture: simultaneous delivery of full field of view and zoomed images

## 2.5 Video

Video frame rate (up to):

31fps @ 1920x1080

42fps @ 1280x1024

### Scaled Resolution:

Scaled Resolution	H	V	Pixel Count	Notes
720p	1280	720	921600	
XVGA	1024	768	786432	ipad 2/ipad mini
DVGA (16:9)	1136	640	727040	iphone 5
DVGA (3:2)	960	640	614400	iphone 4S
SVGA	800	600	480000	
D1 (PAL)	720	576	414720	
4CIF (PAL)	704	576	405504	
D1 (NTSC)	720	480	345600	
4CIF (NTSC)	704	480	337920	
VGA	640	480	307200	
2CIF (PAL)	704	288	202752	
HVGA (4:3)	480	360	172800	
2CIF (NTSC)	704	240	168960	
HVGA (8:3)	640	240	153600	
HVGA (3:2)	480	320	153600	
HVGA (16:9)	480	272	130560	
CIF (PAL)	352	288	101376	
CIF (NTSC)	352	240	84480	
QVGA (SIF)	320	240	76800	
QCIF (PAL)	176	144	25344	

QCIF (NTSC)	176	120	21120	
SQCIF	128	96	12288	

## 2.6 Protocols

- The camera shall have Real Time Streaming Protocol (RTSP) support allowing for compatibility with media players such as Apple QuickTime, VLC Player and others.
- The camera shall support both unicast and multicast communication protocol.
- The camera shall support RTSP, RTP over TCP, RTP over UDP (Unicast/Multicast), HTTP1.0, HTTP1.1, TFTP
- 100 Base-T Ethernet Network Interface
- Multi-streaming: 8 non-identical streams

## 2.7 Electrical

General purpose opto-coupled input and output

Power over Ethernet (PoE): PoE 802.3af

Auxiliary Power 12-48V DC, 24VAC

Power consumption: PoE – Class 0

- AV2225PMIR: 11.3 Watts max (Auxiliary DC power)
- AV2225PMTIR: 10.9 Watts max (Auxiliary DC power)
- AV2225PMIR-S: 12.1 Watts max (Auxiliary DC power)
- AV2225PMTIR-S: 11.8 Watts max (Auxiliary DC power)

## 2.8 Audio Electrical (-A model)

Streaming Two-way

Compression G.711 PCM 8kHz

Input/Output Microphon in / Line out

## 2.9 IR Illuminator

48 pcs 850nm LEDs / 30 meter IR distance (max) / 50° IR angle ( PMIR Model)

4 pcs 850nm LEDs / 60 meter IR distance (max) / 33° IR angle ( PMTIR Model)

## 2.10 Networking

The camera shall be equipped with a 100 Mbps LAN connector.

## 2.11 Environmental

Operating temperature: -40°C (-40 °F) to +50°C (122 °F)

Stable image temperature 0°C (32 °F) to +50°C (122 °F)

Motorized lens operating temperature -20°C (-4°F) to +50°C (122 °F)

Storage temperature -40°C (-40°F) to +60°C (140 °F)

Humidity 0% to 90% (non-condensing)

## 2.12 Minimum Illumination

Color (Day Mode): 0.1 Lux @ F1.2

B/W (Night Mode): 0 Lux, IR sensitive

**2.13 Packaging**

Unit Dimensions:

4.7" H (119mm) x 4.7" W (119mm) x 11.11" D (282mm) / Weight: 3.9 lb (1.76 kg)

Packaged Dimensions:

7.1" H (180mm) x 7.1" W (180mm) x 13.5" D (342.9mm) / Weight: 5.2 lb (2.35 kg)

**2.14 Compatible Accessories**

AV-PMA	Pole mount Adapter
AV-CRMA	Corner Mount Adapter
AV-EBA	Electrical box adapter

**2.15 Related Documents**

AV MegaView® 2 Datasheet

AV MegaView® 2 Installation Manual