

CCTV POWER SUPPLIES

GS-1204 PBF 12 VDC AUTO-RESET THERMAL FUSED

- UL Approved Components
- 4 Output Terminals, up to 1.5 amp/ea
- 3 amps Total Power - Battery Backup

GS-1208 PBF 12 VDC AUTO-RESET THERMAL FUSED

- UL Approved Components
- 8 Output Terminals, up to 1.5 amp/ea
- 3 amps Total Power - Battery Backup

GS-1224 PBF 12 VDC + 24 VAC - DUAL VOLTAGE AUTO-RESET THERMAL FUSED

- UL Approved Components
- 8 DC Output Terminals @ up to 1.5 amps/ea
- 8 AC Output Terminals @ up to 1.5 amps/ea
- DC Circuit - 6 amps total power - battery backup

GS-2404 TPS 24 VAC THERMAL FUSED POWER SUPPLY

- **UL Listed** 
- Thermal Fused Individual Isolated Outputs
- 4 Output Terminals @ up to 1.5 amps/ea
- 6 amps Total Power

GS-2408 TPS 24 VAC THERMAL FUSED POWER SUPPLY

- **UL Listed** 
- Thermal Fused Individual Isolated Outputs
- 8 Output Terminals @ up to 1.5 amps/ea
- 9 amps Total Power

GS-2408 HTPS 24 VAC HIGH POWER THERMAL FUSED POWER SUPPLY

- **UL Listed** 
- Thermal Fused Individual Isolated Outputs
- 8 Output Terminals @ up to 1.5 amps/ea
- 12.5 amps Total Power

GS-2416 TPS 24 VAC THERMAL FUSED POWER SUPPLY

- **UL Listed** 
- Thermal Fused Individual Isolated Outputs
- 16 Output Terminals @ up to 1.5 amps/ea
- 12.5 amps Total Power

GS-2416 HTPS 24 VAC HIGH POWER THERMAL FUSED POWER SUPPLY

- **UL Listed** 
- Thermal Fused Individual Isolated Outputs
- 16 Output Terminals @ up to 1.5 amps/ea
- 25 amps Total Power



GS-2404 TPS



GS-2416 HTPS



Power Supply Cans Include:

- Conduit 1/2" Knock-Outs
- Power Cable 1/2" Grip
- Cam-Lock & Key
- Power Cable Termination Speed-Nuts

Can Sizes: H x W x D

- GS-1204 PBF 15.75" x 12.25" x 4.75"
- GS-1208 PBF 15.75" x 12.25" x 4.75"
- GS-1224 PBF 15.75" x 12.25" x 4.75"
- GS-2404 TPS 11.1" x 8.5" x 3.7"
- GS-2408 TPS 11.1" x 8.5" x 3.7"
- GS-2408 HTPS 11.1" x 8.5" x 3.7"
- GS-2416 TPS 13.2" x 12.6" x 3.7"
- GS-2416 HTPS 12.9" x 12.6" x 3.7"

GLASS LENSES

GS-358 AIF

1/3" DC Auto-Iris

- Vari-Focal 3.5 - 8.0 mm



GS-660 AIF

1/3" DC Auto-Iris

- Vari-Focal 6.0 - 60 mm

GS-2810 AIF

1/3" DC Auto-Iris

- Vari-Focal 2.8 - 10 mm

MONITORS

GS-LCDF-417

LCD TFT 17" CCTV MONITOR WITH V-POD CCTV VIDEO ENHANCING TECHNOLOGY

- 17" Active Matrix TFT LCD SXGA Display
- OSD and Front Controls
- Includes V-POD (GS-LCD-101S) Video Resolution Enhancing Technology
- Cable / Off Air Ready TV Tuner
- Computer VGA interface

GS-LCDF-419

LCD TFT 19" CCTV MONITOR WITH V-POD CCTV VIDEO ENHANCING TECHNOLOGY

- 19" Active Matrix TFT LCD SXGA Display
- OSD and Front Controls
- Includes V-POD (GS-LCD-101S) Video Resolution Enhancing Technology
- Cable / Off Air Ready TV Tuner
- Computer VGA Interface
- Remote Control
- Stereo Speakers



VIDEO ACCESSORIES

GS-LCD 101S (V-POD)

CCTV ENHANCED VIDEO PROCESSOR WITH COMPUTER INTERFACE & TV TUNER

- Enhances video resolution and color
- VGA type Output
- BNC, RCA, S-Video, Audio inputs
- Cable / Off Air ready TV Tuner
- Remote Control / batteries included
- DC plug in adapter included

